

AQUANAMI

2020 OPERATOR'S GUIDE

Includes Safety, Watercraft and Maintenance Information

WARNING

Read this guide thoroughly before operating. It contains important safety information. Minimum recommended operator's age: 16 years old.

Disregarding any of the safety precautions and instructions contained in this Operator's Guide and on-product safety labels could cause injury including the possibility of death!

FOREWORD

Congratulations on your purchase of a new AQUANAMI watercraft. It is backed by the AQUANAMI limited warranty. We are committed to your satisfaction. If you need more complete servicing information, please ask your dealer.

Know Before You Go

To learn how to reduce the risk for you or other persons being injured or killed, read the following sections before you operate the watercraft:

- SAFETY INFORMATION

- WATERCRAFT INFORMATION

Read and understand all safety labels on your watercraft. Failure to follow the warnings contained in this Operator's Guide can result in serious injury or death.

AQUANAMI highly recommends that you take a safe boating course. Please check with your dealer or local authorities for availability in your area.

Get familiar with this watercraft; it may exceed the performance of other motorized watercrafts and PWCs you have ridden.

Safety Messages

This Operator's Guide utilizes the following symbols and words to emphasize particular information:

A WARNING Indicates a potential danger! Failure to follow WARNING instructions could result in serious injury or death.

CAUTION: Indicates special precaution, if not followed, could severely damage the watercraft.

NOTE: Provides key information to make information clearer.

For your safety, understand and follow all the safety precautions and instructions contained in this OPERATOR'S GUIDE. Failure to do so can result in SEVERE INJURY OR DEATH

About this Operator's Guide

This Operator's Guide has been prepared to acquaint the owner/operator or passenger with this watercraft and its various controls, maintenance and safe riding instructions.

Keep this Operator's Guide in the watercraft in a waterproof bag so you can refer to it for operation, instructing others, maintenance and troubleshooting.

AQUANAMI thrives to continuously improve this product. Due to modifications or improvements, some differences between the manufactured product and the descriptions and/or specifications in this guide may occur. AQUANAMI may discontinue or change specifications, designs, features, models or equipment without notice.

TABLE OF CONTENTS

FORWARD1
Know Before You Go1
Safety Messages1
About this Operator's Guide2
TABLE OF CONTENTS
SECTION 1: SAFETY INFORMATION7
GENERAL PRECAUTIONS
Avoid Carbon Monoxide Poisoning8
Avoid Gasoline Fires and Other Hazards8
Avoid Burns from Hot Parts9
Accessories and Modifications9
SPECIAL SAFETY MESSAGES 10
Reminders Regarding Safe Operation10
Before Getting Underway11
Operator and Passenger Awareness11
Drugs and Alcohol12
Hypothermia13
Safe Boating Courses
SAFETY EQUIPMENT
Required Safety Equipment14
Recommended Protective Gear14
Personal Flotation Devices (PFDs)14
Additional Recommended Equipment15
PRACTICE EXERCISES
Where to Practice Exercises
Practice Exercises
Important Factors Not to Neglect17
NAVIGATION RULES
Operating Rules
Navigation System

Collision Avoidance	. 19
FUELING	. 20
Fuel Requirements	. 21
Recommended Fuel	. 21
ON-PRODUCT LABELS	. 22
Watercraft Safety Labels	. 22
Compliance Labels	. 25
PRE-RIDE INSPECTION	. 27
What to Do After Launching the Watercraft	. 32
SECTION 2: WATERCRAFT INFORMATION	.33
CONTROL	. 34
EQUIPMENT	. 37
SECTION 3: OPERATION	.46
OIL AND FUEL	. 47
BREAK-IN PERIOD	. 50
Operation During Break-In Period	. 50
OPERATING INSTRUCTIONS	. 51
Propulsion Principle	. 51
Turn Left and Right	. 51
Boarding the Watercraft	. 52
Starting Engine	. 53
Riding	. 53
Stopping/Docking	. 54
Shutting Off the Engine	. 54
SPECIAL PROCEDURES	. 55
Water in Carburetor	. 55
Water in Engine Breathing Oil Retainer	. 55
Fuel-Flooded Engine	. 56
Jet Pump Water Intake and Impeller Cleaning	. 56
Capsized Watercraft	. 57
Submerged Watercraft	. 58

Water-Flooded Engine	. 58
SECTION 4: MAINTENANCE INFORMATION	.59
MAINTENANCE SCHEDULE	. 60
MAINTENANCE PROCEDURES	. 64
General Inspection	. 64
Cleaning	. 64
Lubrication and Anticorrosion Protection	. 65
Engine	. 66
Exhaust System	. 67
Fuel System	. 69
Electrical System	. 69
WATERCRAFT CARE	. 76
Post – Operation Care	. 76
STORAGE	. 78
Propulsion System	. 78
Fuel System	. 78
Engine and Exhaust System	. 79
Electrical System	. 79
Body and Hull	. 79
Repairs	. 80
PRE-SEASON PREPARATION	. 81
Pre-Season Preparation Chart	. 81
SECTION 5: TECHNICAL INFORMATION	.83
WATERCRAFT IDENTIFICATION	. 84
Hull Identification Number	. 84
Engine Identification Number	. 84
ENGINE EMISSIONS INFORMATION	. 85
Emission Control Information	. 86
SPECIFICATION	. 87
SECTION 6: TROUBLESHOOTING	.89
TROUBLESHOOTING GUIDELINES	. 90

SECTION 7: LIMITTED WARRANTY	93
AQUANAMI LIMITED WARRANTY	
US EPA EMISSION-RELATED WARRANTY	
SECTION 8: CUSTOMER INFORMATION	99

SECTION 1: SAFETY INFORMATION

GENERAL PRECAUTIONS

Avoid Carbon Monoxide Poisoning

All gasoline engine exhaust contains carbon monoxide, a deadly gas. Breathing carbon monoxide can cause headaches, dizziness, drowsiness, nausea, confusion and eventually death. Carbon monoxide is a colorless, odorless, tasteless gas that may be present even if you do not see or smell any engine exhaust. Deadly levels of carbon monoxide can collect rapidly, and you can quickly be overcome and unable to save yourself. Also, deadly levels of carbon monoxide can linger for hours or days in enclosed or poorly ventilated areas. If you experience any symptoms of carbon monoxide poisoning, leave the area immediately, get fresh air and seek medical treatment. To prevent serious injury or death from carbon monoxide:

- Never run the watercraft in poorly ventilated, enclosed or partially enclosed areas such as watercraft houses, seawalls or other boats in close proximity. Even if you try to ventilate engine exhaust, carbon monoxide can rapidly reach dangerous levels.
- Never run the watercraft where engine exhaust can be drawn into a building through openings such as windows and doors.
- Never stand behind the watercraft while the engine is running. A person standing behind a running engine may inhale high concentrations of exhaust fumes. Inhalation of concentrated exhaust fumes that contain carbon monoxide can result in CO poisoning, serious health problems and death.

Avoid Gasoline Fires and Other Hazards

Gasoline is extremely flammable and highly explosive. Fuel vapors can spread and be ignited by a spark or flame many feet away from the engine.

To reduce the risk of fire or explosion, follow these instructions:

- Use only an approved red gasoline container to store fuel.
- Strictly adhere to the instructions in FUELING section.
- Never start watercraft if gasoline or gasoline vapor odors are present in the engine compartment.
- Never start or operate the engine if the fuel cap is not properly secured.
- Do not carry gasoline containers in the storage bin or anywhere else on the watercraft. Gasoline is poisonous and can cause injury or death.
- Never siphon gasoline with your mouth.
- If you swallow gasoline, get any in your eyes, or inhale gasoline vapors, see a doctor immediately.

If gasoline is spilled on you, wash thoroughly with soap and water and change your clothes.

Avoid Burns from Hot Parts

Certain components may become hot during or after operation. Avoid contact during and shortly after operation to avoid burns.

Accessories and Modifications

Do not make unauthorized modifications, or use accessories that are not approved by AQUANAMI. Since these changes have not been tested by AQUANAMI, they may increase the risk of accidents, injuries, and or death and violate local, state or federal law. See your authorized AQUANAMI dealer for available accessories for your watercraft.

SPECIAL SAFETY MESSAGES

Reminders Regarding Safe Operation

The performance of this watercraft may be different than other watercraft you may have operated. Make sure you read and understand the content of this Operator's Guide to become completely familiar with the controls and operation of the watercraft before embarking on your first trip, or taking on a passenger. If you have not had the opportunity to do so, practice driving solo in a suitable traffic free area to become accustomed to the feel and response of this watercraft. Be fully familiar with all controls before accelerating above idle speed.

Always keep in mind that as the throttle lever is returned to the idle position, less directional control is available. To turn the watercraft, both steering and throttle are necessary. Do not release throttle when trying to steer away from objects. Your need throttle to steer. If the engine is shut off, directional control is lost.

This watercraft does not have A REVERSE GEAR OR BRAKING DEVICE. ALWAYS APPROACH LAND, DOCKS, SWIMMERS OR HAZARDS SLOWLY AND WITH CAUTION TO AVOID DAMAGE TO THE WATERCRAFT OR INJURY TO THE OPERATOR, PASSENGERS OR OTHER PERSONS.

Do not store any objects in areas that are not designed specifically for storage. Riding with passenger makes the watercraft handle differently and requires greater skill.

Combustion engines need air to operate; consequently this watercraft cannot be totally watertight. Any maneuvers such as turning constantly in tight circles, plunging the bow through waves, or capsizing the watercraft, that cause the air inlet openings to be under water may cause severe engine damage due to water ingestion. Refer to OPERATING INSTRUCTIONS subsection and the LIMITED WARRANTY section contained in this Operator's Guide.

Engine exhaust contains carbon monoxide (CO), which can cause serious health problems or death if inhaled in sufficient quantities. Do not operate the watercraft in a confined area or allow CO to accumulate around the watercraft, or in enclosed or sheltered areas.

Know the waters in which the watercraft is to be operated. Current, tides, rapids, hidden obstacles, wakes and waves etc. can affect safe operation and handling of this watercraft.

It is not advisable to operate the watercraft in rough waters or inclement weather. In shallow water, proceed with caution and at very low speeds. Grounding or abrupt stops may result in injury and/or watercraft damage. Debris may also be picked up and thrown rearward by the jet pump onto persons or property.

Keep the tether cord attached to the operator's PFD or wrist (wrist strap required) at all times and keep it free from snagging on the joystick to help insure that the engine stops should the operator fall off. After riding, remove the tether cord from the engine cut-off switch to avoid unauthorized use by children or others. If the operator falls off the watercraft and the tether cord is not attached as recommended, the watercraft engine will not stop.

Ride within your limits and level of riding ability. Always ride responsibly and safely. Use common sense and courtesy. Respect the environment and the rights of other users of the waterways.

Avoid riding in very rough waters or practicing extreme maneuvers like jumping wakes or waves.

Before Getting Underway

For safety reasons and proper care, always perform the pre-ride inspection as specified in your Operator's Guide before operating your watercraft.

Do not exceed the weight or passenger capacities for your watercraft. Overloading can affect maneuverability, stability and performance. Also, heavy seas reduce capacity.

Regularly inspect the watercraft, hull, engine, safety equipment, and all other boating gear and keep them in safe operating condition prior to and after each use.

Be sure you have the minimum required safety equipment, PFDs and any additional gear needed before every use.

Ensure that all lifesaving equipment, including fire extinguisher (not supplied with vehicle), are in safe operating condition and easily accessible.

Keep an eye on the weather. Check local weather broadcasts before departure. Be alert to changing conditions. Keep accurate and up-to-date charts of the boating area on board. Before getting underway, check water conditions in the planned boating area.

Ensure there is enough fuel on board for each planned trip. Always verify fuel level before use and during the ride. Apply the principle of 1/3 of the fuel to reach your destination, 1/3 to return, and keep 1/3 in reserve. Allow for changes due to adverse weather or other delays.

Operator and Passenger Awareness

Read and understand all safety labels on the watercraft, the Operator's Guide, and all other safety documents before operating the watercraft.

Respect and follow all applicable laws. Check local and federal boating laws applicable to the waterways where you intend to use your watercraft. Learn the local navigation rules. Know and

understand the applicable navigation system (such as buoys and signs). Remember that sun, wind, fatigue or Illness may impair your judgment and reaction time.

Operation of this watercraft by a person under 16 years of age, or a person with a disability that impairs vision, reaction time, judgment, or operation of this watercraft is NOT recommended.

Always properly use the tether cord when operating the watercraft. Ensure that any operator and passenger knows how to swim and how to re-board the watercraft from the water.

Boarding in deep water can be strenuous. Practice in chest-deep water before operating or using your watercraft in deep water. Ensure that any operator and passenger wear a PFD at all times.

Never accelerate or run the watercraft while someone is near the rear of watercraft. Keep away from steering moving parts (nozzle). Do not start the engine or operate the watercraft if anyone is in close proximity to the watercraft, or near the rear of the watercraft

Keep away from the intake grate while the engine is running. Items such as long hair, loose clothing, or PFD straps can become entangled or trapped in the impeller or water pump.

Before re-boarding, make sure engine is off and the tether cord is removed from the engine cut-off switch.

To prevent accidental starting, always remove the tether cord from the engine cut-off switch when persons are boarding, nearby, or during removal of any weeds or debris from the intake grate.

Minors should always be supervised by an adult whenever operating this watercraft. Laws regarding the minimum age and licensing requirements of minors may vary from one jurisdiction to another. Be sure to contact the local boating authorities for information regarding the legal operation of this watercraft in the intended jurisdiction of use.

Drugs and Alcohol

Never use drugs or alcohol while operating this watercraft. Like driving a car, driving a watercraft requires the operator to be sober, attentive and alert. Operating a watercraft while intoxicated or under the influence of drugs is not only dangerous, but also illegal. These laws are vigorously enforced. The use of drugs and alcohol, singly or in combination, decreases reaction time, impedes judgment, impairs vision, and inhibits your ability to safely operate this watercraft.

Alcohol consumption and boating do not mix! Operating with the use of drugs or alcohol endangers the lives of your passengers, other boaters, and yourself. Federal laws prohibit operating a watercraft with the use of drugs or alcohol.

Hypothermia

Hypothermia, the loss of body heat resulting in a subnormal body temperature, is a significant cause of death in boating accidents. After an individual has succumbed to hypothermia, he or she will lose consciousness and then drown. PFDs can increase survival time because of the insulation they provide. Naturally, the warmer the water, the less insulation one will require. When operating in cold water (below 4°C (40°F)) consideration should be given to using a coat or jacket style PFD as they cover more body area than the vest style PFDs.

Some points to remember about hypothermia protection:

- While afloat in the water, do not attempt to swim unless it is to reach a nearby watercraft, fellow survivor, or a floating object onto which you can grab or climb. Unnecessary swimming increases the rate of body heat loss. In cold water, drown-proof methods that require putting your head in the water are not recommended. Keep your head out of the water. This will greatly lessen heat loss and increase your survival time.
- Maintain a positive attitude about your survival and rescue. This will improve your chances of extending your survival time until you can be rescued. Your will to live does make a difference!
- If there is more than one person in the water, huddling together is recommended. This action tends to reduce the rate of heat loss and thus increase the survival time.
- Always wear your PFD. It won't help you fight off the effects of hypothermia if you don't have it on when you go into the water.

Safe Boating Courses

Many areas or states recommend or require a boating safety course. Check with your local authorities. Check local and federal boating laws applicable to the waterways where you intend to use your watercraft. Learn the local navigation rules. Know and understand the applicable navigation system in your area (such as buoys and signs).

SAFETY EQUIPMENT

Required Safety Equipment

The operator and the passenger must wear an approved Personal Flotation Device (PDF) that is suitable for PWC use.

As the owner of the watercraft, you are responsible for assuring that all required safety equipment is aboard.

Check state and local regulations about required safety equipment. Safety equipment required by regulations is mandatory.

Minimum requirements include the following (not supplied with this vehicle):

- Personal flotation devices (PFDs)
- A buoyant heaving line of 15m (50 ft) minimum
- A watertight flashlight or approved flares Signaling device
- Sound producing devices (air horn or whistle).
- Fire extinguisher.

Recommended Protective Gear

The operator and passenger should wear protective gear, including:

- A wet suit bottom or thick tightly woven and snug fitting clothing that provides equivalent protection. Severe internal injuries can occur if water is forced into body cavities as a result of falling in the water or being near jet thrust nozzle.
- Footwear. Some type of lightweight, flexible foot protection is recommended. This will help reduce possible injury, should you step on sharp underwater objects.

Personal Flotation Devices (PFDs)

Each person on a recreational watercraft must wear a personal flotation device (PFD) at all times. Ensure that these PFDs meet all regulations.

A PFD provides buoyancy to help keep the head and face above the water, and to help maintain a satisfactory body position while in the water. Body weight and age should be considered when selecting a PFD. The buoyancy provided by the PFD should support your weight in water. The size of the PFD should be appropriate for the wearer.

Body weight and chest size are common methods used to size PFDs. It is your responsibility to ensure that you have the proper number and types of PFDs on board to comply with federal and local regulations, and that you and your passenger wear them at all times.

Additional Recommended Equipment

It is recommended that you acquire additional equipment for safe, enjoyable cruising. This list, which is not all inclusive, includes items you should consider acquiring.

- Local map
- First aid kit
- Tow rope
- Flares
- Mooring cords
- Portable waterproof VHF radio

A cellular telephone in a waterproof bag or container has also been found to be beneficial to boaters when in distress.

PRACTICE EXERCISES

It is always a good idea to practice and get familiar with all controls, functions and handling characteristics of your watercraft before venturing on the water.

Always secure the tether cord to the engine cut-off switch and the clip to your PFD or your wrist.

Where to Practice Exercises

Find a suitable area to practice the exercises. Ensure the area meet the following requirements:

- No traffic
- No obstacles
- No swimmers
- No current
- Ample space to maneuver
- Adequate water depth

Practice Exercises

Practice alone the following exercises.

<u>Turning</u>

Practice turning in circles in both directions at slow speed. When comfortable with the exercise, increase difficulty by making some figure 8. When this is mastered, repeat the above exercises but at increased speed.

Stopping Distances

Practice stopping the watercraft in a straight line at different speeds. Remember, water drag is the main factor which reduces the watercraft speed and thus the stopping distance.

NOTE: The watercraft speed, load, current and wind also play an important role in affecting stopping distances.

Avoiding an Obstacle

Practice obstacle avoidance (choose a virtual point on the water) by steering the watercraft and maintaining throttle. Repeat exercise, but this time release throttle while turning.

NOTE: With this exercise, you will learn that you need throttle to steer the watercraft in a different direction.

<u>Docking</u>

NOTE: You can use the start and stop button to reduce the docking speed.

Practice docking using the throttle and steering to become familiar with the response of the watercraft and to develop good control skills. It is recommended that you use a paddle to dock the watercraft to prevent damage to the watercraft and avoid injuries.

Important Factors Not to Neglect

In addition, always remember that the following conditions have a direct impact on how your watercraft will behave and respond to different conditions:

- Loads
- Currents
- Wind
- Water conditions

Make sure to be alert to these conditions, and adapt accordingly. For delicate maneuvers, the best advice is always to try to reduce your speed.

NAVIGATION RULES

Operating Rules

Operating a watercraft can be compared with driving on unmarked highways and roads. To prevent collisions or avoid other boaters, a system of operating rules must be followed. It's not only common sense, it's the law!

Generally, keep to your right and safely avoid collisions by keeping a safe distance from other watercraft, boats, people and objects.

The following illustration identifies different parts of a boat that are used as directional reference points, the bow being the front of the boat. Your watercraft is not designed to be operated at night or in poor visibility conditions.



Crossing Situations: Give right of way to craft ahead and to your right. Never cross in front of a boat.

Overtaking Situations: Give right of way to other craft and keep clear.

Navigation System

Navigational aids, such as signs or buoys, can assist you in identifying safe waters. Buoys will indicate whether you should keep to the right (starboard) or to the left (port) of the buoy, or to which channel you can continue. They may also indicate whether you are entering a restricted or controlled area such as a no wake or low speed zone. They may also indicate hazards or pertinent boating information. Markers may be located on shore or on the water. They can also indicate speed limits, no power craft or boating, anchorage and other useful information. (The shape of each type of marker will provide assistance).

Make sure you know and understand the navigation system applicable to the waterways where you intend to use the watercraft.

Collision Avoidance

Do not release the throttle when trying to steer away from an obstacle. Engine power and jet pump thrust is required to steer the watercraft.

Always keep a constant lookout for other persons, obstacles, other boats or objects in the water, especially when turning. Be alert for conditions that may limit your visibility or block your vision of others.

Respect the rights of other recreationists and/or bystanders and always keep a safe distance from all other watercraft, boats, people and objects.

Do not wake or wave jump, ride the surf line or attempt to spray or splash others with your watercraft. You may misjudge the ability of the watercraft or your own riding skills and strike a boat, watercraft or person.

This watercraft has the capability of turning sharper than other boats. Do not initiate sharp, high speed turns. Such maneuvers are dangerous and make it hard for others to avoid you or understand where you are going. Also, you and/or your passenger(s) could be thrown from the watercraft.

FUELING

Always verify fuel level before, during and after each use.

Always stop the engine before fueling and never allow anyone to remain on the watercraft while fueling. Always remember that fuel is flammable and explosive under certain conditions. Do not smoke or allow open flames or sparks in the vicinity of gasoline.

Fuel is flammable and explosive under certain conditions. Always work in a well ventilated area. Do not smoke or allow open flames or sparks in the vicinity.

Follow these safe boating fueling instructions carefully:

- Turn off engine.
- Do not insert the spout too far in filler neck.
- Pour fuel slowly so that air can escape from the tank and prevent fuel flow back. Be careful not to spill fuel.
- Fully tighten fuel tank cap.

- · Always stop the engine before refueling.
- Fuel is flammable and explosive under certain conditions.
- Always work in a well ventilated area. Do not smoke or allow open flames or sparks in the vicinity.
- Fuel tank may be pressurized, turn cap slowly when opening.
- When fueling, keep watercraft level.
- Do not overfill or top off the fuel tank and leave watercraft in the sun. As temperature increases, fuel expands and might overflow.
- Always wipe off any fuel spillage from the watercraft. Periodically verify fuel system.

After refueling, always ensure there is no gasoline vapor odor inside the engine compartment.

Fuel Requirements

NOTICE: Always use fresh gasoline. Gasoline will oxidize; the result is loss of octane, volatile compounds, and the production of gum and varnish deposits which can damage the fuel system.

Even if gasoline containing greater than ten volume percent ethanol is readily available, the US EPA has issued a prohibition against the use of gasoline containing greater than 10% ethanol that applies to this product. The use of gasoline containing greater than 10% ethanol with this engine may harm the emission control system and will void the warranty.

Use of fuel containing ethanol above the percentage specified by government regulations is not recommended and can result in the following problems in the fuel system components:

- Starting and operating difficulties.
- Deterioration of rubber or plastic parts.
- Corrosion of metal parts.
- Damage to internal engine parts.

Inspect frequently for the presence of fuel leaks or other fuel system abnormalities if you suspect the presence of ethanol in gasoline exceeds the current government regulations.

Alcohol blended fuels attract and hold moisture which may lead to fuel phase separation and can result in engine performance problems or engine damage.

Recommended Fuel

- RECOMMEND PREMIUM UNLEADED GASOLINE 91 PUMP OCTANE OR HIGHER
- MINIMUM UNLEADED GASOLINE 86 PUMP OCTANE OR HIGHER

NOTE: Do not mix oil with fuel.

NOTICE: Never experiment with other fuels. Engine or fuel system damages may occur with the use of an inadequate fuel.

ON-PRODUCT LABELS

Watercraft Safety Labels

The following labels are on your watercraft. If missing or damaged, the labels can be replaced free of charge. See an authorized AQUANAMI dealer. Please read the following labels carefully before operating this watercraft.

NOTE: In the event of any discrepancy between this guide and the watercraft, the safety labels on the watercraft have precedence over the labels in this guide.

Label 1

WARNING To reduce the risk of SEVERE INJURY or DEATH: WEAR A PERSONAL FLOTATION DEVICE (PFD). All riders must wear a Coast Guard approved PFD. WEAR PROTECTIVE CLOTHING. Severe internal injuries can occur if water is forced into body cavities as a result of falling into water or being near jet thrust nozzle. All riders must wear a wet suit bottom or clothing that provides equivalent protection. KNOW BOATING LAWS: The boat is recommended only for operators 16 and older with valid motor vehicle license. Adults must supervise use by minors. You must know and follow all federal, state and local boating laws. ATTACH ENGINE SHUT-OFF CORD (LANYARD) to wrist and keep it free from obstacles so that engine stops if operator falls off. After riding, remove cord from the boat to avoid unauthorized use by children or others. TAKE EARLY ACTION to avoid collisions. Remember boats do not have brakes. Operate defensively at safe speeds and keep a safe distance away from people, objects, and other boats. See Owner's Manual for steering and operation of the boat. RIDE WITHIN YOUR LIMITS AND AVOID AGGRESSIVE MANEUVERS to reduce the risk of loss of control, ejection, and collision. This is a high performance boat - not a toy. Sharp turns or jumping wakes or waves can increase the risk of back/spinal injury (paralysis), facial injuries, and broken legs, ankles, and other bones. Do not jump wakes or waves. DO NOT APPLY THROTTLE WHEN ANYONE IS AT REAR OF BOAT. Turn engine off or keep engine at idle. Water and/or debris exiting jet thrust nozzle can cause severe injury. KEEP AWAY FROM INTAKE GRATE while engine is on. Items such as long hair, loose clothing, or PFD straps can become entangled in moving parts resulting severe injury or drowning. STOP ENGINE BEFORE REMOVING DEBRIS FROM JET INTAKE on bottom of hull. DO NOT TRAVEL FAR AWAY without another watercraft or boat with you. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL.

Label 2



Label 3

- RECOMMEND PREMIUM UNLEADED GASOLINE 91 PUMP OCTANE OR HIGHER
- MINIMUM UNLEADED GASOLINE 86 PUMP OCTANE OR HIGHER

Label 4



 Do not start engine if there is a fuel leak or a loose electrical connection.

Label 5

CAUTION

SAFETY WARNING

Powerboarding can be dangerous and physically demanding. The User of this product should understand that participating in powerboarding may involve serious injury or death. Observe the following safety standards when using the product:

- Get paddlesports instruction from a licensed or certified instructor.
- Obtain certified first aid and rescue training and carry first aid and rescue equipment.
- Always wear a nationally approved personal floatation device.
- Always wear a helmet where appropriate.
- Dress appropriately for weather conditions; cold water and/or weather can result in hypothermia.
- Check your equipment prior to each use for signs of wear or failure.
- Never paddle alone.
- Do not paddle in flood conditions.
- Be aware of appropriate river water levels, tidal changes, dangerous currents and weather changes.
- Scout unfamiliar waters; portage where appropriate.
- · Do not exceed your paddling ability, be aware of your limitations.
- Consult your physician prior to beginning paddlesport training.
- DO NOT use alcohol or mind altering drugs prior to or while using this product.
- Follow the manufacturer's recommendations for the use of this product.
- If additional outing is added to this craft, use manufacturer approved materials only, do not impair entry or exit access.

READ OWNER'S INFORMATION PACKAGE PRIOR TO USING THIS PRODUCT.

The use of this product acknowledges both an understanding and an assumption of the risk involved in powerboarding.

Label 6

AFTER OPERATION

After removing from the water:

- · Flush drive system and hull with fresh water.
- Connect a garden hose to flush heat exchanger and exhaust system for 15 seconds.
- Start the engine for 10 seconds to drain any left over water in the exhaust system. Do not run the engine over 4000 rpm on land.

Compliance Labels

Label 7

THIS BOAT IS NOT REQUIRED TO COMPLY WITH THE FOLLOWING U.S.COAST GUARD SAFETY STANDARDS IN EFFECT ON THE DATE OF CERTIFICATION:

- Display of Capacity Information
- Safe Loading
- Flotation
- Fuel System
- Powered Ventilation
 AS AUTHORIZED BY U.S. COAST GUARD GRANT
 OF EXEMPTION (CGB 11-004-2)
 AQUNAMI,LLC.

Label 8



Label 9

	SSION CONTROL
THIS MARINE SI ENGINE CON EPA EXHAUST REGULATIONS	
ENGINE FAMILY: FAQNM.2952GA	
SPARK PLUG: NGK DR8EA	SPARK PLUG GAP: 0.6 - 0.7 mm
DISPLACEMENT: 0.295 L	FUEL: Unleaded Gasoline
IDLE SPEED: 1600 ± 200 rpm	POWER: 11.0 kW
EXHAUST EMISSION CONTROL: EN	И, ECM
SEE OPERATOR'S GUIDE FOR MAIN	ITENANCE SPECIFICATIONS.

Label 10

Model: IP75 Serial No:	
Model Year: 2015	CE
4 STROKES	נכ
Max Power: 11kW	Max RPM: 6000
Aquanami, LLC., 809 Grar Hampstead, NC, USA.	ndview Dr.,

PRE-RIDE INSPECTION

A WARNING

Perform a pre-ride inspection before each ride to detect potential problems during operation. The pre-ride inspection can help you monitor wear and deterioration before they become a problem. Correct any problems that you discover to reduce the risk of a breakdown or crash.

Before performing the pre-ride inspection, read and understand the CONTROLS section.

What to Do Before Launching the Watercraft

Engine should be off and the tether cord cap should always be removed from the engine cut-off switch prior to verifying any of the following points. Only start watercraft once all items have been checked and operate properly.

No	ITEM	TO DO	CHECK
1	Start and stop buttons	Check operation	
2	Safety Lanyard	Check operation	
3	Throttle	Check operation	
4	Steering system	Check operation	
5	Exhaust pipe cooling	Check by-pass outlet. Water mist/drops should come out exhaust by-pass outlet	
6	Bilge plugs	Ensure plugs are secured	
7	Battery	Inspect cables and retaining fasteners. Ensure good condition and fully charged	
8	Fuel tank	Check/refill	
9	Engine compartment	Check if any water exists; Check if any signs of water leak; Check fuel line connections for tightness; Verify for any fuel leak/odor as well as oil and coolant leak; Check any loosen parts	
10	Engine oil level	Check/refill	
11	Heat exchanger condition	Check	
12	Carburetor	Periodically drain water or contaminated fuel from the carburetor bowl by loosening the carburetor drain	
13	Fuel water separator bottle	Periodically drain water or contaminated fuel from the bottle	
14	Engine breathing oil retainer	Periodically drain the engine breathing oil retainer bottle to clean oil/water residue.	
15	Jet pump water intake	Inspect/clean	
16	Jet pump water intake seal	Inspect any damage or leak	
17	Hull	Inspect for any damage	
18	Dry storage compartment cover	Ensure they are closed and properly sealed	

Check the items listed in the following table before launching the watercraft:

Engine Start/Stop Button and Safety Lanyard

Make sure that both switches operate properly. Start engine and stop it using each switch individually. Lanyard should be securely attached to the kill switch post; it shuts off electric system and engine when pulled off its post.

- Should the stop/start button not work properly, refer to an authorized Aquanami dealer immediately. Fail to do so may result in SEVERE INJURY OR DEATH.
- Should the safety lanyard be loose or not work properly, replace it immediately in order to avoid unsafe use.

<u>Throttle</u>

Check the throttle lever for free and smooth operation. It should return to its initial position immediately after it is released.

Check throttle lever operation before starting the engine.

Steering System

Check steering operation for free movement with the assistance of another person. When the steering joystick is in the center position, the jet pump nozzle should be in the straight ahead position. Ensure the jet pump nozzle pivots easily.

- Check steering handle and corresponding steering nozzle operation before starting the engine.
- Never turn steering handle while someone is nearby the rear of the watercraft. Keep away from steering moving parts.

Exhaust Pipe Cooling

CAUTION: To ensure it is properly working, check by-pass outlet with engine running and engine being flushed. Water mist/drops should come out exhaust by-pass outlet. If the exhaust from the by-pass is not wet, stop engine and consult your AQUANAMI Dealer. The exhaust pipe is cooled

by water from the jet pump. If the water flow from jet pump to exhaust pipe is blocked, the exhaust pipe and connecting components could be damaged.

CAUTION: Never run the engine without supplying water to the cooling system when watercraft is out of water. If out of water, level the craft. Install a garden hose to the flushing connector, which is also the cooling water exit port when watercraft operates on water.

CAUTION: Failure to flush cooling system, when engine is out of water, may severely damage the exhaust system.

CAUTION: Never run engine longer than 1 minute when watercraft is out of water. Drive line seal has no cooling when watercraft is out of water.

Bilge Plugs

Should water be present in the bilge, press manual bilge pump switch to start the electric bilge pump. If some water remains in bilge, tilt the watercraft to the rear and unscrew drain plugs to completely empty the bilge. Ensure all plugs are securely closed before operating your watercraft.

Battery

Pay attention to battery "+ and "-" signs. Ensure the battery is correctly connected, with terminals tightened and secured.

The battery must always be fully charged and in good condition. Loss of battery power may leave you stranded. Never operate the watercraft if the battery does not have sufficient power or if it shows any other signs of decreased power.

Fuel Tank

With the watercraft leveled, fill the fuel tank. Refer to FUELING section for checking fueling.

Engine Compartment

Check if any water exists in engine compartment. Check for any signs of water leak. Check fuel line connections for tightness. Check for any fuel leak/odor as well as oil and coolant leaks and correct before use. Check and tighten loose parts or connections before use.

Should any leak or gasoline odor be present, do not start the engine. Refer to an authorized Aquanami dealer before use.

Engine Oil Level

Ensure oil level is appropriate. Check for oil leaks on engine and in engine compartment and correct before use.

Check Carburetor

Water or contaminated fuel in carburetor bowl will cause engine to suddenly stop when you depress throttle lever, or you may not be able to start engine. Periodically drain water or contaminated fuel from the carburetor bowl by loosening the carburetor drain screw. Use a cup to collect the drained liquids. Ensure the drain screw is closed after cleaning.

Check Fuel/Water Separator Bottle

Periodically drain water or contaminated fuel from the separator bottle. Use a cup to collect the drained liquids. To drain the contaminated fuel in the separator bottle, simply disconnect the hose from the middle nozzle of the bottle, and let the contaminated fuel drain out from the bottom nozzle through the hose to a cup. Ensure reconnect the drain hose before operating watercraft.

Check engine breathing oil retainer bottle

Check the retainer bottle periodically and clean any oil residue to keep engine breathing freely. To drain the oil/water in the retainer bottle, simply disconnect the hose from the middle nozzle of the bottle, and let the water/oil drain out from the bottom nozzle through the hose to a cup. Reconnect the drain hose back before operating watercraft.

Jet Pump Water Intake

Check the seal between the jet pump intake and the ride plate. A damaged seal will allow air into the jet pump, resulting in loss of propulsion.

Remove weeds, shells, debris or other objects that could restrict the flow of water and damage the cooling system and jet pump. Clean as necessary. If any obstruction cannot be removed, refer to an authorized Aquanami dealer for servicing.

Inspect the leading edges of the impeller for damage. Performance will be greatly reduced if the impeller is nicked, bend or damaged.

Do not inspect the water intake or intake grate without removing the lanyard from the post.

<u>Hull</u>

Inspect hull for cracks, damage or any possible leaks. Check that all seals are in good condition. Lift front end of watercraft to completely drain bilge through the bilge drain plug and replace plugs after draining.

What to Do After Launching the Watercraft

Check the item listed in the following table after launching the watercraft and before operating unit.

ITEM	TO DO	Check
Gauges	Check operation.	

<u>Gauges</u>

Press engine START/STOP button and install the tether cord capon the engine cut-off switch. Ensure all gauges work properly.

SECTION 2: WATERCRAFT INFORMATION

CONTROLS



- 1. <u>Main Switch</u>: The main switch turns on/off power supply from battery to the watercraft electric system. The engine cannot be started when the main switch is off. Always turns off the main switch when the watercraft is not in operation to prevent battery drain.
- 2. <u>Steering handle</u>: The steering handle controls the direction of the watercraft. Turn the handle in the direction of your turn.

- Check steering handle and corresponding steering nozzle operation before starting engine.
- Never turn steering handle while someone is nearby rear of watercraft.
- Keep away from steering moving parts (nozzle, linkage etc.).
- 3. <u>Start Button</u>: To start engine, depress and hold the start button. Release immediately after engine is started.
- 4. <u>Stop Button</u>: To stop engine, fully release throttle lever then depress the stop button. Remember to disconnect safety lanyard from its post.
- 5. <u>Throttle Trigger</u>: When the throttle trigger is squeezed, the watercraft accelerates. When fully released, engine automatically slows down to idle speed and watercraft will gradually slow down. To increase or maintain watercraft speed, squeeze the throttle trigger with your finger. To decrease watercraft speed, release the throttle trigger. The throttle trigger is spring loaded and should return to rest position (idle) when released.

Directional control is reduced when the throttle is released and lost when engine is off.

6. <u>Engine Cut-Off Switch</u>: The tether cord cap must be securely attached to the engine cut-off switch before the engine will start. To stop engine, remove the tether cord cap from the engine cut-off switch.

Always attach the tether cord clip to the operator's personal flotation device (PFD) or wrist (wrist strap required).

7. <u>Engine Tether Cord (Safety Lanyard)</u>: Attach the engine Tether Cord to operator's life vest or wrist so that the engine stops if the operator falls off. Always disconnect safety lanyard when watercraft is not in operation in order to prevent the engine from starting accidentally, and to avoid unauthorized use by children or others or theft.

NOTE: Leaving the safety lanyard on its post when engine is not running will slowly discharge the battery.

While engine can be stopped using the engine stop button, good habits recommend that the Tether Cord also be disconnected when stopping.

8. <u>Information Gauges</u>: When tether cord is plugged in and the start button is depressed once, the information gauges read engine RPM, fuel level and battery life. The engine hour gauge is located inside engine compartment. Once the stop button is depressed or Tether Cord is pulled off, all the gauges will be turned off.

- The fuel level indicator may provide false reading if the watercraft is not leveled.
- After depressing start button, the information gauges are on, which will drain battery if the engine is not running.
- Always remove Tether Cord when the engine is not running. Leave Tether Cord on its post will drain battery dead when engine is not running.
- 9. <u>Manual Bilge Water Pump Switch</u>: The bilge water pump switch is a push button switch to turn on the electric bilge pump to evacuate water from the bilge.

EQUIPMENT (15) (14) (12) (10) (16)(17) (18)(19) 25 16 (23)(29 (32)

10. **<u>Rubber Bumper</u>**: The rubber bumper provides protection to hull.

(18)

11. Not used.

12. <u>Handles</u>: The handles can be used to lift the watercraft. It provides a handhold for the operator and a passenger to hold on to while underway.

13. <u>Foot Brace</u>.

14. Passenger Seat.

15. Driver Passenger Seat.

16. <u>Baffled Air Intake</u>: The baffled air intake allows air into the bilge for ventilation and air supply. It stops water from entering the engine

CAUTION: If water enters the engine compartment under certain circumstances, it may cause severe damage to the engine and prevent safe operation.

17. <u>Fuel Tank Cap</u>: Unscrew the cap counter clockwise. After fueling, reinstall cap and fully tighten.

- Always stop the engine before refueling. Fuel is flammable and explosive under certain conditions.
- Always work in a well ventilated area. Do not smoke or allow open flames or sparks in the vicinity.
- Fuel tank may be pressurized, turn cap slowly when opening.
- When fueling, keep watercraft level.
- Do not overfill or top off the fuel tank and leave watercraft in the sun. As temperature increases, fuel expands and might overflow.
- Always wipe off any fuel spillage from the watercraft.
- · Periodically verify fuel system.
- **18.** <u>Accessory Mounting Base</u>: The accessory mounting base can be used to install accessories and equipment.
- 19. Hull Joint Seam Tape: The hull joint seam tape provides the protection for watercraft hull.
- 20. **<u>Rear Eyelet</u>**: Eyelets can be used for mooring and as tie-down points when trailering your watercraft.
- 21. <u>Control Station</u>: The control station is where the steering handle, main switch, cut-off switch, start/stop buttons and gauges are located. It also provides dry storage space for fire extinguisher, safety devices and personal items.
- **22.** <u>Fire Extinguisher</u>: The control station provides the storage area for fire extinguisher (not supplied with the watercraft).
- 23. <u>Engine Compartment Cover Lock</u>: Turn the lock handle to open the engine compartment cover.

24. Not used.

25. <u>Engine Compartment Cover</u>: The engine compartment cover must be closed and secured when the watercraft is in operation. **NOTE:** The engine compartment cover does not float in water.

- · Components inside engine compartment may be hot.
- When starting or operating the engine, do not touch any electrical part.
- Never leave any object, rag, tool, etc., in the engine compartment or in the bilge.
- 26. <u>Heated Water Outlet/Flush Garden Hose Connector</u>: The heated water outlet/flush garden hose connector has three functions:
 - a. When operating unit, fresh cooling water from jet pump flows through heat exchanger, then exits from this outlet;
 - b. Use this connector to flush the heat exchanger, cooling water passage and exhaust system during cleaning after use;
 - c. Provides cooling water for engine and exhaust system when running the engine out of water.

Do not block the heated water outlet when the watercraft is in operation. Restriction of the heated water flow will damage the engine.

- 27. <u>Exhaust By-Pass Outlet</u>: The engine exhaust emits from this exhaust by-pass outlet at idle speed.
- 28. **<u>Rear Eyelet</u>**: Eyelet can be used for mooring and as tie-down points when trailering your watercraft.

29. Engine Compartment Stainless steel hinge:

- 30. Bilge Pump Water Outlet: Water from bilge pump exits here.
- 31. <u>Fuel Tank Vent</u>: It vents air out from fuel tank when pressure builds up in the tank as temperature rises. The fuel tank breathing check valves are inside the engine compartment.
- 32. Hinge: It allows the control station to be turned over to access the underdeck storage.



33. **Steering Nozzle:** Steering nozzle turns left and right by operating steering handle.

- Check steering handle and corresponding steering nozzle operation before starting.
- Never start engine and never turn steering handle while someone is nearby rear of watercraft.
- Keep away from steering moving parts (nozzle, linkage etc.).
- **34.** <u>Steering Nozzle Linkage</u>: The steering nozzle pivoting linkage turns steering nozzle left and right by operating steering handle.
- 35. **<u>Bilge Drain Plug</u>**: Unscrew drain plug whenever watercraft is on the trailer. This will allow water in the bilge and engine compartment to be evacuated and helps to reduce condensation. Should water be found in the bilge, it can be easily drained by opening the drain plugs when engine is off and watercraft is out of the water. It is suggested to drain bilge when the watercraft is trailered on a ramp.

36. <u>Not used.</u>

CAUTION: Never remove the drain plugs when the watercraft is in the water. Make sure the drain plugs are properly secured prior to launching the watercraft in the water.

37. Jet Pump Water Intake Grate: Water is drawn in through this opening. The water intake grate minimizes the entry of foreign objects into the propulsion system.

Keep away from intake grate while engine is on. Items such as long hair, loose clothing or personal flotation device straps could potentially become entangled in moving parts resulting in severe injury or drowning.









38. No used.

- **39.** <u>CDI:</u> Capacitive Discharge Ignition.
- **40.** <u>Exhaust pipe</u>: Cooling water flows through the double walled exhaust pipe, and enters the water box.
- 41. <u>Carburetor</u>: It regulates the flow of air and fuel mix into the engine cylinder.
- **42.** <u>Exhaust By-Pass Hose</u>: The engine exhaust flows through this exhaust by-pass hose at idle speed.
- 43. Water Box/Muffler: It reduces the amount of noise emitted by the exhaust of the engine.
- 44. Electronic Control Module: It holds CDI and other electronic components.
- 45. Battery Tie: It holds the battery in place.
- 46. **<u>Battery</u>**: Ensure to connect the battery with correct "+" and "-" terminals. Refer to MAINTENANCE section for battery charging and maintenance.
- 47. Electric Regulator: It maintains the voltage of the engine generator power.
- 48. **<u>Bilge Pump</u>**: Bilge pump draws water from bilge when water level sensor detects water or when the bilge pump manual switch is pressed.

49. Not used.

- 50. <u>Air Induct Box and Spark Arrestor</u>: It traps water from entering carburetor and contains the spark arrestor.
- 51. <u>Not used.</u>





Note 1: Disconnect the hose as shown to drain water /oil. Reconnect the hose back after draining

Note 2: Disconnect the hose as shown to drain water /fuel. Reconnect the hose back after draining

52. <u>Fuel Pump</u>: It pumps fuel from fuel tank to carburetor.

53. Fuel filter.

54. Fuel Tank.

55. <u>Fuel pick-up and fuel sensor assembly</u>: The fuel pick up hose and fuel sensor are inside the fuel tank.

56. Oil filter.

- 57. Fuel Tank Breath-In Check Valve: It allows air to flow into fuel tank.
- 58. <u>Fuel Water Separator</u>: It retains water or contaminated fuel. Check the bottle periodically and drain water or contaminated fuel to keep engine running with clean fuel. To drain water or contaminated fuel in the separator bottle, simply disconnect the hose from the middle nozzle of the bottle, and let the contaminated fuel drain out from the bottom nozzle through the hose to a cup. Reinstall the hose after draining.
- 59. <u>Fuel Tank Vent Check Valve</u>: It vents air out from fuel tank when pressure builds up in the tank as temperature rises. This is a one-way valve.
- 60. Engine Breathing Oil Retainer Bottle: It retains oil mist and oil from engine breathing path. Check the bottle periodically and clean any oil residue to keep engine breathing freely. To drain the oil/water in the retainer bottle, simply disconnect the hose from the middle nozzle of the bottle, and let the water/oil drain out from the bottom nozzle through the hose to a cup. Reinstall the hose back after draining.







- 61. <u>Engine Oil Filling Cap and Oil Dipstick</u>: It allows adding oil in the engine when required. Dipstick indicates the engine oil level.
- 62. <u>Carburetor drain screw: Use a wrench to drain water or contaminated fuel from the</u> <u>carburetor bowl. Be sure to close the drain screw after cleaning.Carburetor Drain Hose</u>: Use a cup to drain water or contaminated fuel.
- 63. Carburetor balance pipe
- 64. Drive Shaft Damper and Coupling.
- 65. Drive Shaft to Hull Seal Boot.
- 66. **Fresh Water Supply Hose**: It supplies fresh water from jet pump to cool heat exchanger and exhaust system.
- 67. <u>Siphon Hose</u>: It connects siphon pump head to jet pump. Siphon pump head evacuates water in bilge by the low pressure generated in jet pump. Check and clean the vacuum siphon pump head, remove any blocking objects periodically.

SECTION 3: OPERATION

OIL AND FUEL

Engine Oil

This watercraft is equipped with a 4-stroke engine that requires 4-stroke motor oil for internal engine lubrication.

CAUTION: Never use any 2-stroke engine oil.

Recommended Oil: Use a 4-stroke, 10W30 grade motor oil.

🖄 WARNING

Engine oil may be hot. Certain components in the engine compartment may be very hot. Direct contact may result in skin burn.

<u>Oil Level</u>

CAUTION: Check oil level frequently and refill if necessary. Do not overfill. it would make the engine smoke and reduce its power. Operating the engine with an improper oil level may severely damage engine.

Before checking the oil level on this engine, watercraft must be level. Check oil level either with watercraft in water or out of water. Engine should be warm. Start engine for 20 seconds to warm up oil if necessary. Reinstall dipstick, push in completely. Remove dipstick and read oil level. It should be between marks.

Use a funnel to add oil. You may find it is helpful to attach 12MM ($\frac{1}{2}$ in) ID hose of 6 inches long to the funnel for filling oil. Add the recommended oil to the proper level. Do not overfill.

Every time oil is added in engine, do following steps to ensure correct oil level:

- 1. Start engine, idling for 20 seconds, then stop engine.
- 2. Wait for 1 minute then, rechecking the oil level. This is required to allow the oil to flow evenly in the oil chambers. Otherwise, you will have a false oil level reading.

Changing Oil

You must change engine oil according to Maintenance Schedule in Section 4. Oil drain plug is located at the boat stern. Make sure that engine is off and warm, but NOT HOT. Make sure the drain plug is properly secured after oil change. No oil leaking!

Gasoline

Using gasoline mixed with a stabilizer like STA-BIL, to extend the shelf-life of the gas, fill the fuel tank before each use so you don't run out while mowing.

NOTICE: Always use fresh gasoline. Gasoline will oxidize; the result is loss of octane, volatile compounds, and the production of gum and varnish deposits which can damage the fuel system.

Always verify fuel level before, during and after each use.

RECOMMEND PREMIUM UNLEADED GASOLINE 91 PUMP OCTANE OR HIGHER

- MINIMUM UNLEADED GASOLINE 86 PUMP OCTANE OR HIGHER
- NOTE: Do not mix oil with fuel.

\land WARNING

Follow these safe boating fueling instructions carefully:

- Turn off engine.
- · Do not insert the spout too far in filler neck.
- Pour fuel slowly so that air can escape from the tank and prevent fuel flow back. Be careful not to spill fuel.
- · Fully tighten fuel tank cap.

A WARNING

- · Always stop the engine before refueling.
- · Fuel is flammable and explosive under certain conditions.
- Always work in a well ventilated area. Do not smoke or allow open flames or sparks in the vicinity.
- · Fuel tank may be pressurized, turn cap slowly when opening.
- When fueling, keep watercraft level.
- Do not overfill or top off the fuel tank and leave watercraft in the sun. As temperature increases, fuel expands and might overflow.
- Always wipe off any fuel spillage from the watercraft. Periodically verify fuel system.

BREAK-IN PERIOD

Operation During Break-In Period

Your watercraft is equipped with a 4 stroke closed loop water cooled engine. Having a break-in period is crucial to its proper performance and the product life. The engine break-in period allows various components of the engine to wear and polish themselves to the correct operation clearances and conditions. The scheduled oil change during the break-in period is also required. It will prevent excessive wear and damage to the components. Failure to perform the required break-in period may significantly handicap your craft performance, and shorten the product life. In certain circumstances, it may void your warranty.

A break-in period of 6 operating hours is recommended before running the watercraft at sustained full throttle. During this period, maximum throttle should not exceed 1/2 to 3/4 opening. However, brief full acceleration and speed variations contribute to a satisfactory break-in.

NOTICES:

- Continued wide open throttle accelerations or prolonged cruising speeds are detrimental to the watercraft during the break-in period.
- YOU MUST CHANGE ENGINE OIL AND REPLACE OIL FILTER AFTER THE FIRST 10 HOURS OF OPERATION.

It is highly recommended that after the first 10 hours of operation, the watercraft be checked by an authorized Aquanami dealer. This inspection will also provide the opportunity to discuss the unanswered questions you may have encountered during the first hours of operation.

OPERATING INSTRUCTIONS

Always perform the PRE-RIDE INSPECTION before operating this watercraft. Be sure to read the SAFETY INFORMATION and the WATERCRAFTINFORMATION sections.

Should any control or instruction not be fully understood, refer to an authorized Aquanami dealer.

Propulsion Principle

The engine is directly coupled to the drive shaft which, in turn, rotates the impeller. The water is drawn up from the jet pump water intake grate underneath the watercraft, then flows through the impeller to the venturi. The venturi accelerates the water and produces thrust to move the watercraft. By depressing the throttle lever, an operator increases engine speed and therefore watercraft speed.

Whenever the engine is to be started, the operator should always be properly sitting on the seat and be wearing protective clothing including a Coast Guard approved PFD and a wet suit bottom.

Keep away from intake grate while engine is on. Items such as long hair, loose clothing or personal flotation device straps could potentially become entangled in moving parts resulting in severe injury or drowning.

Turn Left and Right

Turning the steering joystick pivots the jet pump nozzle which controls the watercraft direction. Turning the joystick to the left will turn the watercraft to the left and inversely. The throttle should be applied to turn the watercraft.

- Throttle should be applied and steering handle turned to change the direction of the watercraft. Unlike a car, a watercraft needs some throttle to turn.
- Practice in a safe area applying the throttle and turning away from an imaginary object. This is a good collision avoidance technique.
- Directional control is reduced when the throttle is released and lost when engine is off.

CAUTION: Combustion engines need air to operate; consequently, this watercraft cannot be totally water tight. Maneuvers that cause the air intake opening to be under water may cause severe engine damage due to water ingestion and unsafe operation.

Boarding the Watercraft

As with any watercraft, boarding should be done carefully and with engine off at all time.

- Engine should be OFF when boarding the watercraft. Keep limbs away from jet or intake grate.
- Inexperienced riders should practice how to get aboard close to shore first before venturing into deep water.

Boarding from a Dock or in Shallow Water

When boarding in shallow water or from a dock, board the watercraft from the side. Ensure there is at least 50 cm (1.5 ft) of water. Once aboard, take the appropriate riding position.

CAUTION: Starting the engine or operating the watercraft in shallow water can draw sand, pebbles, or rocks through the jet pump, which might damage the impeller or other pump components.

Boarding in Deep Water

Swim to the side or front of the watercraft. Pull yourself up onto the watercraft. Once aboard, take the appropriate riding position.

Boarding in deep water can be very difficult, so practicing boarding in shallow water is necessary for safe operation.

Starting Engine

Before unloading the watercraft on to water, it can be started for about 10 seconds to verify proper operation.

Before starting the engine, the operator and passenger should always:

- · Be properly seated on the watercraft
- · Have a firm grip on a handle
- Wear appropriate protective clothing including a PFD approved by local authorities and a wet suit bottom.

NOTICES:

Ensure there is at least 50 cm (1.5 ft) of water when you are onboard prior to starting the engine, otherwise damage to the impeller or other jet pump components might occur. Do not accelerate abruptly.

- 1) Attach the tether cord clip to your PFD or to your wrist (wrist strap required).
- 2) Firmly grip the joystick with your left hand and place both feet on the foot braces.
- 3) Install the tether cord on the engine cut-off switch.
- 4) Depress the engine START button to crank the engine.
- 5) Release engine START button immediately after engine is started.
- 6) If engine fails to start after 15 seconds, wait a few seconds then repeat procedure.

NOTES:

- This engine is designed to start with NO need to depress throttle.
- First time use of the watercraft or prolonged storage will take longer to start. Repeated attempts without depressing the throttle will allow the fuel pump to draw fuel from fuel tank to carburetor first. Excessive depression of the throttle will cause flooding of the carburetor. Wait 15-30 minutes before restarting if the carburetor is flooded.

CAUTION: Do not hold the start button more than 15 seconds to avoid starter overheating. A rest period should be observed between the cranking cycles to let the starter cool down. Be careful not to discharge battery.

Riding

Evenly accelerate to increase speed and reach deeper water. Do not apply full throttle until the engine is warm. The safe use and operation of this watercraft is dependent upon the use of proper riding techniques, as well as upon common sense, good judgment, and expertise of the operator.

Do not apply full throttle until the engine is warm, otherwise you may damage engine cylinder and piston.

- Never attempt to perform jumps or stunts as they could lead to serious injuries or death.
- To make sure your riding position allows you to remain in control and locate any upcoming craft or obstacle.
- Avoid Rough Water or Poor Visibility Operation. The watercraft is not intended for rough water usage. Usage on rough water may result in SEVERE INJURY OR DEATH.

Stopping/Docking

The watercraft is slowed down by water drag. The stopping distance will vary depending on weight, speed, water surface condition, presence and direction of wind and current. The rider should become familiarized with the stopping distance under different conditions. Release the throttle at a sufficient distance before the expected docking area. It is recommended that the operator paddle the watercraft to any dock to prevent damage to the watercraft and to prevent bodily injuries.

Directional control is reduced when the throttle is released and lost when engine is off.

Shutting Off the Engine

To shut off the engine, completely release throttle lever and press the engine stop button. Remove safety lanyard from engine cut-off post.

A WARNING

- Never leave the tether cord on its post when watercraft is not in operation in order to prevent accidental engine starting or to avoid unauthorized use by children or others or theft.
- Leave the tether cord on its post will drain battery dead when engine is not running.

SPECIAL PROCEDURES

Water in Carburetor

Once the water enters the carburetor bowl, the engine will not work properly. When you press the throttle trigger, it may lose power and stop suddenly, or you may not be able to start the engine. When this happens, empty the carburetor and fuel water separator bottle. Use a wrench to loosen the carburetor drain tube (screw #62) to drain the water or contaminated fuel from the carburetor bowl.





Note 1: Disconnect the hose as shown to drain water /oil. Reconnect the hose back after draining

Drain contaminated fuel in the fuel water separator bottle (58) by disconnecting the hose from the middle nipple of the bottle. Use a cup to collect the drained liquids. After cleaning, ensure to tighten the carburetor drain screw and reconnect the hose to the middle nipple of the fuel water separator bottle.

Water in Engine Breathing Oil Retainer Bottle

Over time, water and oil residue accumulate in the engine breathing oil retainer bottle (60). It retains oil mist and oil from engine breathing path. Check the bottle periodically and clean any oil residue to keep engine breathing freely. To drain the oil/water in the retainer bottle, simply disconnect the hose from the middle nozzle of the bottle, and let the water/oil drain out from the bottom nozzle through the hose to a cup. Reinstall the hose after draining.



Note 2: Disconnect the hose as shown to drain water /fuel. Reconnect the hose back after draining

Fuel-Flooded Engine

When the engine does not start after several attempts, the engine may be fuel-flooded. Proceed as follows:

• Open engine cover, and leave it uncovered for 30 minutes. If the engine still does not start, remove the spark plug, let fuel inside cylinder ventilate for 30 minutes, clean spark plug or using a new spark plug, try to start engine.

CAUTION: VEVER RUN ENGINE for more than 30 seconds without supplying water to the exhaust cooling system and heat exchanger when watercraft is out of water.

Jet Pump Water Intake and Impeller Cleaning

Keep away from intake grate while engine is running. Items such as long hair, loose clothing or personal flotation device straps can become entangled in moving parts.

Weeds, shells or debris can get caught on the intake grate, drive shaft and/or impeller. A clogged water intake may cause problems such as:

- Cavitation: Engine speed is high but watercraft moves slowly due to reduced jet thrust. Prolonged running with this problem may cause damage to jet pump components.
- Overheating: Since the jet pump operation controls the flow of water to cool the exhaust system, a clogged intake will cause the exhaust system to overheat and damage exhaust components.

A weed clogged area may be cleaned as follows:

If it is necessary to reach in to remove any foreign object caught in the propulsion system, the tether cord MUSTBE REMOVED from the engine cut-off switch

Manually remove the weeds, shells or debris from the intake grate. Start engine and make sure watercraft operates properly. If system is still blocked, remove the watercraft from the water and clean the intake grate, impeller and jet nozzle.

CAUTION: Inspect water intake grate and impeller for damage. Refer to an authorized Aquanami dealer for repair.

Capsized Watercraft

The watercraft is designed so that it should not turn over easily, however any watercraft can capsize. If watercraft turns over, it will remain capsized.

When watercraft is capsized, do not attempt to restart the engine. Operator and passengers should always wear approved personal flotation devices.

To return the watercraft upright, ensure the engine is off and the Lanyard is NOT on its post.

- In shallow water, lift one side of the watercraft up to upright it.
- In deep water, lean your body on one side and grab the other side of watercraft, then use your body weight to rotate the watercraft in either direction to right it.
- The bilge pump should automatically start to drain water in bilge if water enters the bilge and the main switch is on. If the water sensor failed to start the bilge pump, push the bilge pump

switch to drain the water in the bilge. The lanyard must be connected to its post for the bilge pump to operate.

CAUTION:

- If watercraft has been capsized for LESS THAN 3 minutes, wait until the bilge pump drains the engine compartment. Then start the engine.
- If the watercraft has been capsized for MORE THAN 3 minutes, check engine compartment first. If the engine compartment has less than 3 inches of water, wait until the bilge pump drains the engine compartment. Manually turn on the bilge pump if the water sensor failed to turn on the bilge pump. Then start the engine.
- Do not attempt to crank engine with water in the engine compartment to avoid water ingestion that would damage the engine. Bring the watercraft to the shore and drain the water in the engine compartment as soon as possible.
- If the engine does not start, do not attempt to start engine anymore, otherwise, the engine could be damaged. See an authorized Aquanami dealer as soon as possible.

Submerged Watercraft

To limit damage to the engine, drain engine compartment as soon as possible. If the watercraft has been submerged in salt water, lightly spray engine compartment and all components with fresh water using a garden hose to reduce the salt corroding effect of components.

CAUTION: Never try to crank or start the engine with a submerged watercraft. Water trapped in intake manifold can flow towards the engine and may cause severe damage to the engine. Bring the watercraft to be serviced by an authorized Aquanami dealer as soon as possible.

CAUTION: Delays in servicing the engine will increase engine damage. Failure to have the engine properly serviced as soon as possible may cause sever engine damage.

Water-Flooded Engine

CAUTION: Never try to crank or start the engine with a water-flooded engine. Water trapped in the intake manifold can flow towards the engine and may cause severe damage to the engine. Bring the watercraft to be serviced by an authorized Aquanami dealer as soon as possible.

CAUTION: Delays in servicing the engine will increase engine damage. Failure to have the engine properly serviced as soon as possible may cause severe engine damage.

SECTION 4: MAINTENANCE INFORMATION

MAINTENANCE SCHEDULE

Maintenance is very important for keeping the watercraft in a safe operating condition. The watercraft should be serviced as per the maintenance schedule. A repair shop or person of the owner's choosing may maintain, replace, or repair emission control devices and systems. These instructions do not require components or service by AQUANAMI or authorized AQUANAMI dealers. Although an authorized AQUANAMI dealer has in-depth technical knowledge and tools to service the AQUANAMI watercraft, the emission-related warranty is not conditioned on the use of an authorized AQUANAMI dealer or any other establishment with which AQUANAMI has a commercial relationship. For emission-related warranty claims, AQUANAMI is limiting the diagnosis and repair of emission-related parts to authorized AQUANAMI dealers. For more information, please refer to the US EPA EMISSION-RELATED WARRANTY contained herein. **Proper maintenance is the owner's responsibility**. A warranty claim may be denied if, among other things, the claim was caused by neglect, improper maintenance or improper use.

You must follow the instructions for fuel requirements in the fueling section of this manual. Even if gasoline containing greater than 10% ethanol is readily available, the US EPA has issued a prohibition against the use of gasoline containing greater than 10% ethanol that applies to this product. The use of gasoline containing greater than 10% ethanol with this engine may harm the emission control system and will void the warranty.

- RECOMMEND PREMIUM UNLEADED GASOLINE 91 PUMP OCTANE OR HIGHER
- MINIMUM UNLEADED GASOLINE 86 PUMP OCTANE OR HIGHER

NOTE: Do not mix oil with fuel.

IMPORTANT: Watercraft rental operations or commercial use will require greater frequency of inspection and maintenance.

Maintenance is critical for the safety and longevity of this product. If you are not familiar with safe service practices and adjustment procedures, see your authorized Aquanami dealer. In many instances proper tools and training are required for certain servicing or repair procedures. Never attempt repairs unless the appropriate tools are available. If required, contact your authorized Aquanami dealer for further servicing information. Adhere to the prescribed maintenance schedules to maintain the watercraft and equipment in top condition at all times. An inspection of the watercraft before each use is always recommended.

Carry out all maintenance as listed in the schedule whenever the hours or time of each column is reached.

Failure to properly maintain the watercraft according to the maintenance schedule and procedures can make it unsafe to operate.

The maintenance schedule does not exempt the pre-ride inspection.

Watercraft Maintenance Schedule

PART/TASK	First 10 hours	Every 50 hours or 6 months	Every 100 hours or 12 months	Note
ENGINE	•		•	
Engine oil and filter ⁽¹⁾	R	R ⁽²⁾		(1) Check oil level daily before use.
Corrosion protection (spray an anti-corrosion lubricant to metallic components in engine compartment)	L ⁽³⁾	L ⁽³⁾		(2) Change oil and oil filter if the watercraft capsizes or water enters the engine.
Engine rinsing		C ⁴⁾		(3) Every 10 hours in salt water use.
Engine drive shaft seal ⁽⁵⁾	I	I	L, R	(4) Daily rinsing after salt water use.
Engine support and rubber mount	I	I		(5) Replace oil seal at 200 hours (irrespective of number of years).
Engine breath filter/oil retainer	С	С		See NOTE 1 at the end of maintenance schedule table.
AIR INTAKE SYSTEM	-			
Air induction box	I	I		
Flame arrestor			I, C ⁽¹⁾	(1) Inspect and clean by repair shop.
EXHAUST SYSTEM				•
Exhaust system and fasteners	I, C ⁽¹⁾	I, C	J(2)	(1) Daily flushing after salt water or dirty water use.(2) Inspect by repair shop.
COOLING SYSTEM				
Hose and fasteners	1			
Heat exchangers		1		(1) Check daily before use. Coolant bottle should be kept full.
Coolant ⁽¹⁾ if equipped.			R	
FUEL SYSTEM			I. I.	
Carburetor		C (1), (2)		(1) By repair shop.
Fuel cap, fuel lines, connections, pressure relief valves	I	1	I(1)	(2) Also clean if watercraft capsizes.
Fuel filter		R		
Fuel water separator	С	С]
Throttle cable	I	I, L ⁽¹⁾]
ELECTRICAL		•		
Spark plug		I	R ⁽¹⁾	(1) By repair shop.
Battery and fasteners	I	(2)		(2) Inspect once per month.

PART/TASK	First 10 hours	Every 50 hours or 6 months	Every 100 hours or 12 months	Note		
Electric connectors and fasteners	I	I	I	(3) Daily rinse and clean water sensor switch after salt water use.		
Engine cut-off switch and stop switch	I	I				
Main switch	I	Ι				
Bilge pump automatic sensor switch	C, I ⁽³⁾	I				
Bilge pump and manual switch	I	Ι				
STEERING SYSTEM						
Steering cable and connections	I	I	L ⁽¹⁾	(1) By repair shop.		
Steering nozzle	I	[(1)				
PROPULSION SYSTEM				•		
Jet pump	C ⁽¹⁾			 (1) Daily cleaning jet pump by spraying water in its inlet and outlet and then apply a coat of an anti- corrosion lubricant after salt water use. (2) Replace seals at 200 hours (irrespective of number of years). See NOTE 1 at the end of maintenance schedule table. (3) By repair shop. 		
Drive shaft rubber boot and mechanical seal ⁽²⁾	I	 (3)				
Impeller shaft seal (2)			(3)			
Stator cone cap "O" ring			(3)			
Impeller and impeller wear ring clearance	I	I				
Sacrificial anode (if so equipped)		Ι	R			
Pump mounts	I	Ι				
Ride plate seal	I	(3)				
Hull						
Hull	I	I		(1) Daily rinsing after salt water use.(2) Every 10 hours in salt water use.		
Engine compartment seals	I	I				
Engine compartment]		
(spray water repellent to fiber glass hull in engine compartment)	C ⁽¹⁾ , L ⁽²⁾	$C^{(1)}, L^{(2)}$				
A: ADJUST						
C: CLEAN						
I: INSPECT						
L: LUBRICATE						
R: REPLACE						

Note 1: Inspect for possible leak or damage on oil seal or water seal, and drive shaft sleeve surface.

MAINTENANCE PROCEDURES

This section includes instructions for basic maintenance procedures.

Turn off the engine and follow these maintenance procedures when performing maintenance. If you do not follow proper maintenance procedures you can be injured by hot parts, moving parts, electricity, chemicals or other hazards.

General Inspection

Check engine compartment for any damage and for leaks of fuel, water, coolant or oil. Ensure all hose clamps are properly secured and no hose is cracked, kinked or presenting any other damage.

If any gasoline leak and/or odor are present, do not start the engine. Have the watercraft serviced by an authorized Aquanami dealer.

Inspect muffler, battery and fuel tank. Visually check electrical connections for corrosion and tightness. Inspect hull, jet pump water intake grate and ride plate for damage. Damaged parts must be repaired or replaced.

Should removal of a locking device (e.g. lock tabs, self-locking fasteners, etc.) be required, always replace with a new one.

NOTICE: Never leave any object, rag, tool, etc., in the engine compartment.

Cleaning

The engine compartment should be cleaned to remove any fuel/oil/electrolyte deposits and mildew. Occasionally, wash the interior with water and soap (only use mild detergent). Remove any marine organisms from engine and/or hull. Apply non-abrasive wax such as silicone wax. Lightly spray the engine after salt water use. Clean bilge water pump automatic switch sensor.

Dry engine and engine compartment with clean dry towels. Clean jet pump by spraying water in its inlet and outlet.

CAUTION: Never clean fiberglass and plastic parts with strong detergent, degreasing agent, abrasives, paint thinner or acetone.

Lubrication and Anticorrosion Protection

Throttle Cable

Lubricate the throttle cable with XP-S Lube or equivalent. Depressing and releasing the throttle trigger should operate smoothly. Throttle trigger should return to its initial position without any hesitation. There must be a small amount of free-play when throttle trigger is released. Refer to an authorized Aquanami dealer if necessary.

- Do not alter or tamper with throttle cable adjustment or routing.
- If throttle lever does not automatically return, do not operate watercraft and see your authorized Aquanami dealer.

Electrical Connections

As necessary, apply an anti-corrosion product such as dielectric grease on battery posts and all exposed cable connectors. Additional Lubrication XP-S Lube or equivalent will help prevent corrosion of metallic parts and maintain proper operation of moving mechanisms.

Metallic Components in Engine Compartment

Spray an anti-corrosion lubricant to metallic components in engine compartment for corrosion protection according to Maintenance Chart. For salt water use, spray an anti-corrosion lubricant to metallic components in engine compartment prior to any salt water use, and every 10 hours thereafter.

Engine Compartment Fiber Glass Surface Protection

Spray water repellent on fiber glass surface in engine compartment according to the Maintenance Chart to prevent mildew and marine organisms.

Certain components in the engine compartment may be very hot. Direct contact may result in skin burn. Do not touch any electrical parts or jet pump area when engine is running.

Engine

Engine Oil

Change oil and oil filter according to oil change schedule. This watercraft is equipped with a 4stroke engine that requires 4-stroke motor oil for internal engine lubrication.

Recommended Oil: Use a 4-STROKE SYNTHETIC OIL (summer). If the recommended engine oil is not available, use 5W40 or 10W40 grade motor oil.

CAUTION: Never use any 2-stroke engine oil.

- Oil is flammable. Always wipe off any oil spillage from the bilge.
- Certain components in the engine compartment may be very hot. Direct contact may result in skin burn.

Engine Oil Level

NOTICE: Check oil level frequently and refill if necessary. Do not overfill as it can cause smoke and reduction in power. Operating the engine with an improper level may severely damage the engine and void the warranty.

CAUTION: Certain components in the engine compartment may be very hot. Direct contact may result in skin burn or other injury.

Oil level can be checked with the watercraft either in or out of water. Before checking the oil level on this engine, the watercraft must be level. The engine should be warm. Start the engine for 20 seconds to warm up oil if necessary. Reinstall dipstick and push in completely. Remove dipstick and read oil level. The oil level should be between the indicated marks on the dipstick.

Use a funnel to add oil. You may find it is helpful to attach 12MM (½ in) ID hose of 6 inches long to the funnel for filling oil. Add the recommended oil to the proper level. Do not overfill. Wipe and remove any excess or spilled oil.

Every time oil is added, perform the following steps to ensure correct oil level:

- 1. Start engine, idling for 20 seconds, then stop engine.
- 2. Wait for 2 minutes then recheck the oil level. This is required to allow the oil to flow evenly in the oil chambers and to prevent a false oil level.

The oil change may be performed by an authorized AQUANAMI dealer, repair shop, or person of your own choosing.

Oil Filter

Replace oil filter according to Maintenance Chart. Use AQUANAMI supplied oil filter. The oil filter change may be performed by an authorized AQUANAMI dealer, repair shop, or person of your own choosing.

Engine Breathing Oil Retainer Bottle

Remove and retain oil mist and oil from engine crank case breathing path. Check the bottle periodically and clean any oil residue to keep engine breathing freely and to keep the engine compartment clean.

To drain the oil/water in the retainer bottle, simply disconnect the hose from the middle nozzle of the bottle, and let the water/oil drain out from the bottom nozzle through the hose to a cup. See Engine Breathing Oil Filter and Retainer Bottle component in WATERCRAFT AND MAIN COMPONENTS section.

Engine Drive Shaft Seal

Inspect and if necessary, replace engine drive shaft seal according to Maintenance Chart. Replacing seal should be performed by an authorized AQUANAMI dealer or knowledgeable repair shop.

Exhaust System

Flushing Exhaust and Heat Exchanger

Flushing the exhaust system with fresh water after each use is essential to neutralize corroding effects of salt or other chemical products present in water. It will also help to remove sand, salt, shells or other particles in water jackets and/or hoses. Flushing should be performed when the

watercraft is not expected to be used further the same day or when the watercraft is stored for any extended period of time.

CAUTION: Properly follow the instructions below.

Proceed as follows:

- 1. Clean ride plate with a water hose.
- 2. Clean jet pump by spraying water in its inlet and outlet.
- 3. Connect a garden hose to the heat exchanger and exhaust flushing connector located at the rear of the watercraft. Do not open the water tap and do not start the engine yet.
- 4. To flush heat exchanger and exhaust cooling system, start the engine then immediately open water tap.
- 5. Run the engine about 30 seconds at a fast idle between 3000 4000 RPM.
- 6. Disconnect the garden hose first, and keep the engine running another 10 seconds.
- 7. Stop the engine.

CAUTION:

- Never flush a hot engine.
- Always start the engine before opening the water tap.
- Open water tap immediately after engine is started to prevent overheating.
- Never run engine without supplying water to the exhaust cooling system when watercraft is out of water.
- Never run engine longer than 1 minute. Drive line seal has no cooling when watercraft is out of water.
- Always close the water tap before stopping the engine.

Running water into the flush system before the engine is running may result in engine damage and will void the warranty.

Fuel System

- Gasoline is highly flammable and explosive. Failure to check and repair for any fuel leakage could resulting in fire or explosion, which can cause severe injury or death.
- Shut off engine and remove the Lanyard from its post.
- Do not smoke. And keep away any fire or sparks.
- · Fuel line is pressurized. Fuel can spray out and cause accident.
- Do not attempt to run engine with fuel line disconnected.

Carburetor Cleaning

Water or contaminated fuel in carburetor bowl may cause the engine to suddenly stop, not start or run erratically. Drain carburetor to remove any possible water in the carburetor bowl. Open the carburetor drain screw at the bottom of the carburetor. Use a bottle to collect the soiled/watered gas in the carburetor bowl. Close the drain screw after cleaning.

The carburetor should be cleaned using carburetor cleaner according to the Maintenance Chart or after watercraft capsizes. Carburetor cleaning should be performed by an authorized Aquanami dealer.

Electrical System

Engine Start/Stop Button and Safety Lanyard

Make sure that both switches operate properly. Start engine and stop it using each switch individually. Lanyard should be securely attached to the kill switch post. Inspect Engine Start/Stop Button and Safety Lanyard according to the Maintenance Chart.

- Should the stop/start button not work properly, refer to an authorized Aquanami dealer immediately. Failure to do so may result in SEVERE INJURY OR DEATH.
- Should the safety lanyard become loose or not work properly, replace it immediately in order to avoid unsafe use.

Bilge Pump Automatic Sensor Switch

Make sure the bilge pump automatic sensor switch operates properly. Test the automatic sensor switch by adding clean water to bilge. Bilge pump should start to run when water level reaches approximately 2 inches.

Bilge Pump and Manual Switch

Make sure the bilge pump and manual switch operate properly. Depressing the manual switch with the lanyard attached to its post should operate the bilge pump.

Battery

Pay attention to battery "+ and "-" signs. Ensure the battery is correctly connected, tightened and secured.

The battery must always be fully charged and in good condition. Loss of battery power may leave you stranded. Never operate the watercraft if the battery does not have sufficient power or if it shows any other signs of decreased power.

Battery Cleaning

Clean the battery casing, cables and battery posts using a solution of baking soda and water. Remove corrosion from battery cable terminals and battery posts using a firm wire brush. Battery top should be cleaned with a soft brush and any grease-cutting soap or baking soda solution. Rinse with clear water then dry.

Battery Inspection

Visually inspect battery casing for cracks, leaks or other possible damages. Discoloration, warping or a raised top indicates that the battery has overheated or been overcharged.

If the casing is damaged, replace battery and thoroughly clean battery tray and surrounding area with a water and baking soda solution.

CAUTION: Should the battery casing be damaged, wear a suitable pair of non-absorbent gloves when removing the battery by hand.

Inspect the battery posts for secure mounting.
Battery Storage

NOTICE: Battery storage is critical for battery life. Regularly charging the battery during storage will prevent cell sulfation. Keeping the battery in the watercraft for storage may lead to contacts degradation/corrosion and case damage if freezing occurs.

A discharged battery will freeze and crack in areas where freezing conditions are experienced. Electrolyte leakage can damage surrounding parts. Always remove battery from watercraft for storage and regularly recharge it to keep an optimal condition. Clean battery terminals and cable connections using a wire brush. Apply a light coat of dielectric grease on terminals.

Clean battery casing using a solution of baking soda and water. Rinse battery with clear water and dry using a clean cloth.

Store battery in a cool dry place. Such conditions reduce self-discharging and keep fluid evaporation to a minimum. Keep battery away from dew, high moisture and direct sunlight.

Recharge frequency depends on battery condition and storage temperature. Maintain battery as per following table.

AMBIENT TEMPERATURE	CHARGING FREQUENCY
Below 16°C (60°F)	Every month
Above 16°C (60°F)	Every 2 weeks

NOTE: The battery must always be stored in a fully charged state.

Charging a Battery

Never charge or boost the battery while installed in the watercraft.

Always wear safety glasses and charge the battery in a ventilated area. Never charge or boost a battery while installed on a vehicle. Do not open the sealed caps during charging. Do not place battery near an open flame.

NOTICE: If the battery becomes hot to the touch, stop charging and allow it to cool before continuing.

NOTE: Sealed VRLA batteries have an internal safety valve. If battery pressure increases due to overcharging, the valve opens to release excess pressure, preventing battery damage. Carry out a battery UNLOADED VOLTMETER TEST as described in this subsection, then proceed as described below.

An automatic charger is the fastest and most convenient way for error-proof charging. When using a constant current charger, charge battery according to the chart below.

50 minutes

10A

0		
	TIME	CHARGE
STANDARD CHARGING (RECOMMENDED)	4-9 hours	2A

Battery Voltage Below 12.8 V and Above 11.5 V:

QUICK CHARGING

Battery Voltage Below 11.5 V:

A battery with a voltage below 11.5 V requires a special procedure to recharge. In charging an over discharged battery, its internal resistance may be too high to charge at a normal charging rate.

Set charger to the 10 A charging rate and monitor charging current for approximately 30 minutes. If there is no change in charging current or battery becomes abnormally hot, the battery is most likely at the end of its service life and should be replaced.

Battery Maintenance

These batteries require little maintenance to perform perfectly. Follow this simple check list for optimum battery performance:

- Check voltage every 3 months using a voltmeter.
- Keep a battery fully charged to 100% (12.8 V or higher after standing 2 hours).
- Check and charge battery if the voltage drops below 12.5 V.
- Keep the battery top free of grime.
- Clean terminals and connectors if necessary.
- For storage, pull battery or disconnect battery cables.

Spark Plug

Spark plug can degrade over time. Inspect spark plug according to maintenance chart. Replace bad spark plug.

Spark Plug Removal

- Disconnect the ignition coil input connector from spark plug.
- Remove spark plug by using a spark plug socket.

Never remove an ignition coil from a spark plug without disconnecting it from the wiring harness. Flammable vapors may be present in the bilge. Should the tether cord be installed on the engine cut-off switch, a spark could be generated at the coil spark plug end which could cause an explosion.

- Clean the spark plug and cylinder head with pressurized air.
- Unscrew spark plug then use the ignition coil to take spark plug out of spark plug hole.

Spark Plug Installation

Prior to installation, ensure the contact surfaces of the cylinder head and spark plug are free of grime.

Do not adjust gap on this type of spark plug. The adjustment could weaken negative electrodes which may lead to electrode breaking and severe engine damage.

- 1. Using a wire feeler gauge, check electrode gap.
- 2. Apply LOCTITE 767 (ANTISEIZE LUBRICANT) over the spark plug threads to prevent possible seizure.
- 3. Hand screw spark plug into cylinder head. Then, tighten the spark plug clockwise with an approved spark plug socket.
- 4. Install ignition coil. Refer to Ignition Coil Installation.

Ignition Coil

Replacing an ignition coil shall be performed by an authorized AQUANAMI dealer.

Electric Fuse/Circuit Breaker

If the electric bilge pump does not start, check the electric fuse/circuit breaker located inside electric control box. If a fuse is blown, replace by one of the same rating. Replace electric fuse or reset circuit breaker button only after the root cause of the problem has been found and corrected.

- Do not use a higher rated fuse as this can cause severe damage.
- If a fuse has burnt out, the source of the malfunction should be determined and corrected before restarting. See an authorized AQUANAMI dealer for servicing.

Steering System

Check steering mechanism to ensure steering operates smoothly. There should be no excessive play in the system. Refer to an authorized Aquanami dealer if necessary. Check and lubricate steering cable and rotating mechanism by an authorized AQUANAMI dealer according to the Maintenance Chart.

Propulsion System

Remove the Lanyard from its post to prevent accidental engine starting before inspecting and cleaning the jet pump system. Clean the jet pump by spraying water in its inlet and outlet and then apply a coat of an anti-corrosion lubricant for corrosion protection after salt water use. Inspect impeller, intake grate and ride plate, for any damage and replace any damaged part before operating the unit. Inspect and tighten all fasteners. Clean and lubricate for corrosion prevention. Inspect propulsion system according to the Maintenance Chart.

Automatic vacuum siphon pump uses a low pressure area in the jet pump to siphon the water out of the bilge when the engine is operating. Inspect the pump head for obstruction and clean as necessary.

Inspect and replace sacrificial anode if equipped.

<u>Hull</u>

Clean hull and engine area after every salt water use. Rinse watercraft engine area with fresh water. Never use a high pressure washer to clean the engine compartment. USE LOW PRESSURE ONLY (such as a garden hose). High pressure can cause damages to electrical or mechanical systems. Inspect hull for cracks and any possible leaks. Check that all seals are in good condition. Lift front end of watercraft to completely drain engine compartment through the bilge drain plugs.

Anticorrosion Treatment

Wipe off any residual water in the engine compartment. Spray an anti-corrosion lubricant on metallic components in engine compartment while minimizing Overspray for corrosion protection.

NOTE: Engine compartment cover should be left partially open during storage. This will prevent engine compartment condensation and possible corrosion.

WATERCRAFT CARE

Post – Operation Care

Allow engine to cool before performing any maintenance.

General Care

Take the watercraft out of the water every day to prevent marine organism growth. Should any water be present in the engine compartment, open the drain plugs and tilt the front of the watercraft up in order to allow water to flow out. **Remember to always close the drain plugs before placing the unit in water.** Wipe off any remaining water in the engine compartment (engine, battery, etc.) with clean dry rags (this is particularly important in salt water operation).

Take additional care and cleaning if the unit has been used in foul or salt water. Cleaning should occur immediately after salt or foul water use. Rinse off watercraft's engine compartment with fresh water. Rinse and clean bilge water pump automatic sensor switch.

CAUTION: Failure to perform proper care such as: watercraft rinsing, exhaust cooling system flushing or anticorrosion treatment, when watercraft is used in salt or foul water may result in damage to the watercraft and its components.

NOTICES:

- Never leave the watercraft stowed in direct sunlight.
- Engine compartment cover should be left partially open when not in use. This will prevent engine compartment condensation and possible corrosion.

Heat Exchanger and Exhaust Cooling System Flushing

Flushing the exhaust system with fresh water after each use is essential to neutralize corroding effects of salt or other chemical products present in water. It will also help to remove sand, salt, shells or other particles in water jackets and/or hoses. Flushing should be performed when the watercraft is not expected to be used further the same day or when the watercraft is stored for any extended period of time.

CAUTION: Properly follow the instructions below.

Proceed as follows:

1. Clean ride plate with a water hose.

- 2. Clean jet pump by spraying water in its inlet and outlet.
- 3. Connect a garden hose to the heat exchanger and exhaust flushing connector located at the rear of the watercraft. Do not open the water tap and do not start the engine yet.
- 4. To flush heat exchanger and exhaust cooling system, start the engine then immediately open water tap.
- 5. Run the engine about 30 seconds at a fast idle between 3000 4000 RPM.
- 6. Disconnect the garden hose first, and keep the engine running another 10 seconds.
- 7. Stop the engine.

CAUTIONS:

- 1. Never flush a hot engine.
- 2. Always start the engine before opening the water tap.
- 3. Open water tap immediately after engine is started to prevent overheating.
- 4. Never run engine without supplying water to the exhaust cooling system when watercraft is out of water.
- 5. Never run engine longer than 1 minute. Drive line seal has no cooling when watercraft is out of water.
- 6. Close the water tap, then stop the engine.
- 7. Always close the water tap before stopping the engine.
- 8. Do not start water flow into flush water connector until the engine is started; adding that running water into the flush system without the engine first running will result in engine damage that will not be covered under warranty.

Winterize (JetAngler Pro)

- **1.** Put stabilizer in your gas tank.
- 2. Change fuel filter and engine oil according to the requirements of the maintenance list.
- 3. Connect a garden hose to heat exchanger/cooling flushing connector, to flush the cooling system.
- 4. Open water tap to drain all the water in the engine and cooling system. Reposition the JetAngler Pro for draining. The bow (front) needs to be higher than the stern (rear) so it can be drained properly.
- 5. Disconnect the garden hose first, and keep engine running 10 seconds.
- 6. Remove the battery.

Anticorrosion Treatment

To prevent corrosion, spray a corrosion inhibitor (salt water resistant) over metallic components in engine compartment. Apply dielectric grease (salt water resistant) on battery posts and cable connectors. Spray water repellent on fiber glass surface in engine compartment to prevent mildew and marine organisms according to the Maintenance Chart.

STORAGE

Because fuel and oil are flammable, you should have an authorized AQUANAMI dealer, repair shop, or person of your own choosing to inspect the fuel system integrity as specified in the periodic inspection chart.

It is recommended that the watercraft be serviced by an authorized AQUANAMI dealer, repair shop, or person of your own choosing, however the following operations can be performed by you with a minimum of tools.

NOTE: Carry out the following tasks in the same order as detailed in this section.

NOTICE: Do not run the engine during the storage period.

Propulsion System

Jet Pump Cleaning

Clean jet pump by spraying water in its inlet and outlet and then apply a coat of an anti-corrosion lubricant for corrosion protection.

Always remove tether cord from the engine cut-off switch to prevent unexpected engine starting before cleaning the propulsion system components. Engine must not be running for this operation.

Jet Pump Inspection

Remove jet pump nozzle, open the cone cover of stator shaft, and check if water is present; if so, see your authorized AQUANAMI dealer.

Fuel System

Fuel System Protection

FUEL STABILIZER should be added in the fuel tank every fill up to prevent fuel deterioration, water accumulation from ethanol and fuel system gumming. Follow stabilizer manufacturers' instructions for proper use.

NOTICE: It is highly recommended to add fuel stabilizer to fuel system during storage. Fuel stabilizer should be added prior to engine lubrication and fuel tank top up to ensure fuel system components protection against ethanol and varnish deposits.

NOTICE: Water in the fuel tank or system may cause severe internal damage to the engine and carburetor.

Engine and Exhaust System

Heat Exchanger and Exhaust System Flushing

Perform procedure as described in MAINTENANCE PROCEDURES.

Engine Oil and Filter Replacement

The oil change and filter replacement may be performed by an authorized AQUANAMI dealer, repair shop, or person of your own choosing.

Engine Internal Lubrication

- 1. Disconnect ignition coils from spark plug, then remove spark plug from engine cylinder head, and refer to MAINTENANCE PROCEDURES.
- 2. Spray anti-corrosion lube in spark plug holes.
- 3. Press the engine START button to crank the engine a few turns. This will distribute the oil on the cylinder walls.
- 4. Apply a small amount of anti-seize lubricant on spark plug threads, then reinstall the spark plug in the engine cylinder head. Refer to MAINTENANCE PROCEDURES.
- 5. Install the ignition coils, and refer to MAINTENANCE PROCEDURES.

Electrical System

Battery Removal and Charging

Refer to BATTERY in MAINTENANCE PROCEDURES section.

Body and Hull

Hull Cleaning

Wash the hull with a soap and water solution (use only mild detergent). Rinse thoroughly with fresh water. Remove marine organisms from the hull.

NOTICE: Never clean plastic parts with strong detergent, abrasives, de-greasing agent, paint thinner, acetone, or other strong chemical or petroleum cleaners.

Engine Compartment Cleaning

Clean engine compartment and bilge pump automatic sensor switch using hot water and a mild detergent or with bilge cleaner. Rinse thoroughly. Lift front end of watercraft to completely drain bilge through the bilge drain plug.

NOTE: Engine compartment cover should be left partially open during storage. This will prevent engine compartment condensation and possible corrosion.

Bilge Anticorrosion Treatment

Wipe off any residual water in the engine compartment. Spray an anti-corrosion lubricant to metallic components in engine compartment while minimizing overspray for corrosion protection.

Body and Hull Protection

If the watercraft is to be stored outside, cover it with an opaque tarpaulin to prevent sun rays and grime from oxidation of the fiberglass, gelcoat and degradation of the plastic components.

NOTICE: The watercraft should never be left in water for storage. Never leave the watercraft stored in direct sunlight. Never store watercraft in a plastic bag.

Repairs

If any repairs are needed to body or to the hull, contact your authorized AQUANAMI dealer.

PRE-SEASON PREPARATION

Pre-Season Preparation Chart

Maintenance preparation must be performed in conjunction with PERIODIC MAINTENANCE CHART. Ensure to perform all tasks included in the 100 HOURS OR 1 YEAR column before storage.

NOTE: It is recommended that an authorized AQUANAMI dealer perform preseason maintenance preparation at the same time that any safety-related factory campaigns are performed by the authorized AQUANAMI dealer.

Use the following chart for preseason preparation. Since technical skills and special tools are required, some operations should be performed by an authorized AQUANAMI dealer.

Preseason Preparation Chart

GENERAL	GENERAL Inspection of hull and seals. Lubrication/corrosion protection.	
	Exhaust system condition and fasteners.	Dealer
ENGINE	Condition of seals and fasteners.	Dealer
	Oil level and oil filter.	Dealer
COOLING SYSTEM (If equipped)	Inspection of heat exchangers, coolant level, hoses and components. If antifreeze was not changed for storage, drain and replace with new antifreeze.	Dealer
	Inspection of carburetor. Check throttle vale for smoothness. And check fuel bowl if necessary for possible corrosion or fuel path blocking. Check/lubricate throttle cable.	Dealer
FUEL SYSTEM	Fuel system; fuel filter, check valves, lines and fasteners. Dealer	
	Filler neck, fuel tank and fuel cap condition.	Dealer
	Fuel tank straps.	Operator
	Refill fuel tank.	Operator
	Battery condition/charging and reinstallation.	Dealer
ELECTRICAL	Start, stop, cut-off switch and main switch.	Dealer
SYSTEM	Instrument meters.	Dealer
	Bilge pump automatic sensor	Operator
	Bilge pump and manual sensor	Operator
STEERING SYSTEM	Steering system lubrication/ adjustment/inspection.	Dealer
	Propulsion system inspection.	Dealer
PROPULSION	Inspection of vacuum siphon pump.	Dealer

SECTION 5: TECHNICAL INFORMATION

WATERCRAFT IDENTIFICATION

The main components of the watercraft (engine and hull) are identified by different serial numbers. It may sometimes become necessary to locate these numbers for warranty purposes or to trace the watercraft in the event of theft.

Hull Identification Number (HIN)

The Hull Identification Number (HIN) is engraved on the right hand side of the hull at the rear of watercraft.

It is composed of 12 digits:



Engine Identification Number (EIN)

The EIN is located on the engine case under the air induct manifold.



ENGINE EMISSIONS INFORMATION

Manufacturer's Responsibility

Beginning with 1999 model year engines, PWC manufacturers of marine engines must determine the exhaust emission levels and certify these engines with the United States of America Environmental Protection Agency (EPA). An emissions control information label, showing emission levels and engine specifications, must be placed on each watercraft at the time of manufacture.

Dealer's Responsibility

When performing service on Aquanami watercraft that carries an emissions control information label, replacement or repair of any emission related component must be executed in a manner that maintains emission levels within the prescribed certification standards.

Dealers are not to modify the engine in any manner that would alter the horsepower or allow emission levels to exceed their predetermined factory specifications. Exceptions include manufacturer's prescribed changes.

Owner Responsibility

The owner/operator is required to have engine maintenance performed to maintain emission levels within prescribed certification standards.

The owner/operator is not to, and should not allow anyone to modify the engine in any manner that would alter the horsepower or allow emissions levels to exceed their predetermined factory specifications.

EPA Emission Regulations

All Aquanami watercrafts are certified to the EPA as conforming to the requirements of the regulations for the control of air pollution from new watercraft engines.

The factory procedure for servicing the product must be strictly followed.

The responsibilities listed above are general and in no way a complete listing of the rules and regulations pertaining to the EPA requirements on exhaust emissions for marine products.

For more detailed information on this subject, you may contact:

U.S. Environmental Protection Agency Office of Transportation and Air Quality 1200 Pennsylvania Ave. NW Mail Code 6403J Washington D.C. 20460 <u>EPA INTERNETWEB SITE:</u> <u>http://www.epa.gov/otag</u>

Emission Control Information

This marine SI engine complies with U.S. EPA Exhaust Regulations for 2016. The emission label is attached on the top of the engine crankcase.

EMISSION CONTROL AQUANAMI INFORMATION THIS MARINE SI ENGINE COMPLIES WITH U.S. EPA EXHAUST REGULATIONS FOR 2016.		
ENGINE FAMILY: FAQNM.2952GA		
SPARK PLUG: NGK DR8EA	SPARK PLUG GAP: 0.6 - 0.7 mm	
DISPLACEMENT: 0.295 L	FUEL: Unleaded Gasoline	
IDLE SPEED: 1600 ± 200 rpm	POWER: 11.0 kW	
EXHAUST EMISSION CONTROL: EM, ECM		
SEE OPERATOR'S GUIDE FOR MAINTENANCE SPECIFICATIONS.		

SPECIFICATIONS

2020 MODEL JETANGLER SPECIFICATION

CAPACITY			
Max Number of People (v seat):		2	
Recommended Max Load:	160 kg	350 lbs	
DIMENSIONS, WEIGHT	AND RECOMMENDED MAXIMU	IM LOADS	
Length	380 cm	149.6ir	
Width	103 cm	40.5 in	
Height	41 cm	16.1 ir	
Dry Weight	138 kg	303.6 Ibs	
PERFORMANCE			
Max Speed ^[2]	40 km/h	25 mph	
Fuel Assumption at Full Throttle	5 L/h	1.32 gal/h	
Run Time at Full Throttle	Approxima	Approximately 2 hours	
ENGINE			
Туре	4 si	troke	
Declared Power ^[1]	11kW	15 hp	
Number of Cylinders		1	
Displacement	295 cc	18 in ³	
Bore	75 mm	2.95 in	
Stroke	66.8 mm	2.63 in	
Compression Ratio		10:1	
Start	Electi	ric start	
Ignition	Туре	CDI	
Spark plug	NGK	DR8EA	
Spark plug gap	0.6 - 0.7	0.0236 - 0.0276	

Valve clearance (Cold)			
Intake	0.09 mm	0.0035 in	
Exhaust	0.12 mm	0.0047 in	
FUEL SYSTEM			
Fuel Tank Capacity	14 liters	3.7 gal	
COOLING SYSTEM			
Engine Cooling	Closed loop water	cooled	
Oil Cooling	Heat exchanger co from jet pump	Heat exchanger cooled by water flow from jet pump	
Exhaust Cooling	Inject water coolec jet pump	Inject water cooled by water flow from	
Engine Coolant Quantity	1.72 liters	1.82 q	
LUBRICATION SYSTEM			
Lubrication	Туре	Oil sump	
Engine Oil Quantity	2.2 liters	2.32 q	
PROPULSION SYSTEM			
Jet pump	Туре	Axial flow, single stage	
Transmission	Туре	Direct drive	

1) Maximum speed varies depending on weight, wind and current conditions.

2) Declared power as per ISO 8665 at propeller-shaft.

3) Aquanami reserves the right to make changes in design and specifications and/or to make additions to, or improvements in its products without imposing any obligation to install them on its products previously manufactured.

SECTION 6: TROUBLESHOOTING

TROUBLESHOOTING GUIDELINES

Use this section to check for the possible cause of simple problems you may have with your watercraft. You may solve some of the problems rather quickly, but may need help from a skilled mechanical technician. In such cases, refer to an authorized Aquanami Dealer for servicing. If a procedure for replacement or repair is not described in the Guide, have an Authorized Aquanami Dealer perform necessary service.

TROUBLE	POSSIBLE CAUSE	REMEDY
Engine does not turn over	main switch is off	turn on main switch
	Lanyard is not in place	Connect Lanyard on post
	blown fuse	check and replace
	battery runs down, bad terminal connection	charge battery and tighten terminal
	fault start motor	refer to a Aquanami dealer
	bad electrical connectors of start motor cables	refer to a Aquanami dealer
	seized jet pump	refer to a Aquanami dealer
	water flooded and seized engine	refer to a Aquanami dealer
	faulty stop button, faulty Lanyard post	refer to a Aquanami dealer
	bad start switch	refer to a Aquanami dealer
	bad relay switch	refer to a Aquanami dealer
Engine turns slowly, but does not start	weak or discharged battery	replace battery
	bad battery cable connection	tighten
	worn start motor	refer to a Aquanami dealer
Engine turns normally, but does not start	empty fuel	fill
	stale or contaminated fuel tank	clean and refill
	watered/contaminated carburetor	drain carburetor, and drain fuel retainer
	fouled or defective spark plug	replace

Trouble Shooting Guidelines

TROUBLE	POSSIBLE CAUSE	REMEDY
	spark plug cap not connected or loose	tighten
	fuel flooded engine	refer to a Aquanami dealer
	water flooded engine	refer to a Aquanami dealer
	disconnected or faulty fuel pump	refer to a Aquanami dealer
	defective electronic control box	refer to a Aquanami dealer
	bad electrical connectors	Clean and dry the connectors
Engine runs irregularly or stalls	empty, stale or contaminated fuel	siphon tank and refill
	watered carburetor and watered fuel retainer	drain carburetor bowl and drain fuel retainer
	fouled or defective spark plug	replace
	electric wire loose connection or bad connectors	tighten, or see a Aquanami dealer.
	defective electric control box	refer to a Aquanami dealer
Weak spark plug	fouled or weak spark plug	replace
	faulty ignition coils (inside electronic control box)	refer to a Aquanami dealer
Engine smoke	oil too high	drain excessive oil
	internal engine damage	refer to a Aquanami dealer
	coolant too low; coolant leak; damaged cooling system	fill coolant (If your unit has internal cooling)
Engine overheat	coolant low; clogged exhaust cooling system; coolant leak; damaged cooling system; clogged jet	fill coolant; flushing exhaust cooling system; clean jet; or refer to a Aquanami dealer (If your unit has internal cooling)
Watercraft cannot reach top speed, engine does not have power	weeds and debris trapped inside jet	remove and clean
	water or contaminated fuel in carburetor bowl and fuel retainer	drain and clear
	watered or contaminated fuel	clean and refill
	damaged impeller	refer to a Aquanami dealer
	air leak between ride plate and intake pipe, damaged water intake seal	refer to a Aquanami dealer
	weak spark plug	replace

TROUBLE	POSSIBLE CAUSE	REMEDY
	damaged engine by water injection	refer to a Aquanami dealer
	engine oil level too high	drain oil and check
	blocked engine breathing hose; blocked shut off valve	clean and remove blockage
	foul throttle trigger	refer to a Aquanami dealer
	person and cargo weight is too heavy	follow loading capacity
Abnormal vibration	misalignment at the coupler between engine output shaft and jet drive shaft	refer to a Aquanami dealer
Water in engine compartment	engine compartment cover not properly closed	install cover properly
	bad seal	replace
	automatic siphon pump head is blocked	clean
	fouled bilge pump	replace bilge pump
	bad drive shaft mechanic seal	refer to a Aquanami dealer
	hull leak	refer to a Aquanami dealer
	loose drain plug	tighten
	bad air intake valve	check and replace

SECTION 7: LIMITED WARRANTY

LIMITED WARRANTY

Congratulations on choosing an Aquanami personal fishing craft (the "Product"). Aquanami, LLC ("Aquanami") is pleased to extend this Limited Warranty on the Product on the terms and conditions set forth below. You will be deemed to have accepted this Limited Warranty upon the earlier of your purchase or acceptance of delivery of the Product. Please take the time to read and become familiar with this Limited Warranty. IN PARTICULAR, THIS LIMITED WARRANTY REQUIRES THAT ANY DISPUTES BETWEEN YOU AND AQUANAMI MUST BE RESOLVED THROUGH THE DISPUTE RESOLUTION PROCESS DESCRIBED BELOW WHICH INCLUDES BINDING ARBITRATION AND A CLASS ACTION WAIVER.

Who is entitled to this Limited Warranty?

Aquanami extends this Limited Warranty to the original retail purchaser of the Product from Aquanami or one of its independent authorized dealers located in the United States of America (a "Dealer"). If you transfer ownership of the Product during the Warranty Period (as defined below), you may transfer your rights and obligations under this Limited Warranty for the remaining portion of the Warranty Period (as defined below) to the new owner of the Product by delivering a completed Aquanami warranty transfer form to Aquanami within thirty (30) days following the date of such transfer of ownership. Please contact Aquanami or your Dealer for a current version of the warranty transfer form and instructions on processing the warranty transfer. Otherwise, this Limited Warranty is non-transferable.

What is covered by this Limited Warranty?

If the Product is purchased/used for personal, non-commercial use, then Aquanami warrants to you that, for a period of one

(1) year from the date of purchase of the Product by the original retail purchaser, the Product will be free from defects in materials and workmanship, subject to the exclusions described below.

If the Product is purchased/used for commercial use, then Aquanami warrants to you that, for a period of ninety (90) days from the date of purchase of the Product by the original retail purchaser, the Product will be free from defects in materials and workmanship, subject to the exclusions described below.

The applicable warranty period referenced above with respect to the Product is referred to as the "Warranty Period". A Product is considered to be purchased/used for "commercial use" if, at any time during the Warranty Period, (a) the Product has commercial tags or is otherwise licensed/registered for commercial use or (b) the Product is used in connection with any income generating activities of any kind, including, without limitation, rental, employment or work activities. NO PERSON IS AUTHORIZED TO MODIFY, AMEND OR EXTEND THIS LIMITED WARRANTY, OR PROVIDE ANY ADDITIONAL OR DIFFERENT WARRANTIES OR GUARANTEES, ON BEHALF OF AQUANAMI OR ITS AFFILIATES.

What is NOT covered by this Limited Warranty?

You are responsible for ensuring that the Product is properly operated, maintained, handled, stored and used as specified in the applicable Aquanami Operator's Guide (including any updates). In particular, and as a condition to your warranty coverage, you must ensure that the "break-in period" and routine maintenance procedures specified in Operator's Guide are timely adhered to and performed.

This Limited Warranty does not apply to or otherwise cover any defect, failure, loss or damage to the Product due to:

- a) improper operation, maintenance, handling, storage or use (including, without limitation, any failure to adhere to the provisions specified in the Operator's Guide);
- b) accident, misuse, abuse or neglect (including, without limitation, any (i) collision or impact with any object, (ii) customer-applied chemicals or accidental spills, or (iii) water submersion or ingestion of any water or object into the engine);
- c) use of improper or contaminated lubricants, oils and/or fuel;
- d) improper alteration or modification (including, without limitation, any installation of unauthorized/improper attachments, accessories or replacement parts);
- e) subjecting the Product to conditions outside of its design limitations, including, without limitation, racing, speeding or other competitive activities;

- f) failure to comply with any recall or request for repair;
- g) cosmetic imperfections, defects or damage with respect to gel coat finishes and other surface coatings, including without limitation, discoloration, blisters, crazing, and fiberglass delamination];
- h) fire, theft, freezing, vandalism, lightning, hail storms, natural disaster, or any act of God;
- i) normal wear and tear or deterioration;
- j) any damage to the engine or component parts due to ethanol;
- k) damage caused by growth of organisms on or in motor, impeller, water pump or hull surfaces;
- I) parts replaced due to normal wear and tear, including, without limitation, spark plugs, impellers, anodes and carburetors; or
- m) tune-ups or rebuilding of any component parts.

This Limited Warranty applies only to a new Product (and not a used, reconditioned or demo version) if purchased and registered/licensed for use in the United States of America. For the avoidance of doubt, Product components and consumables that require replacement/replenishment due to regular maintenance and/or normal wear and tear (such as oil, lubricants, belts, filters, fuel, etc.) are not covered by this Limited Warranty.

What will Aquanami do to correct a covered defect in the Product?

In the event that a covered defect in the Product occurs during the Warranty Period, and you properly make a warranty claim within the Warranty Period, Aquanami will, at its sole discretion, either (a) repair the defective Product or (b) provide a replacement for the defective Product. Any replacement Product will be the closest then-available equivalent to the original Product, and may not exactly match the original Product. The Limited Warranty on any repaired or replacement Product (including, without limitation, any repaired or replaced component part) will extend for the remaining portion of the Warranty Period applicable to the original Product. If a replacement Product is provided (or replacement component parts are provided as part of a repair), then you agree that the defective Product/component parts become the property of Aquanami and you will execute any documents necessary to transfer title to such items to Aquanami.

What must you do in order to make a warranty claim and obtain warranty service?

During the Warranty Period, you may make a claim for warranty coverage by (a) delivering the claimed defective Product (or component part) to the nearest Dealer, or to Aquanami' warranty service center located at 10600 West Sam Houston Parkway South, Suite 100, Houston, Taxes 77099, and authorizing the Dealer/Aquanami to inspect, investigate, and repair the item as necessary, (b) notifying the Dealer/Aquanami of the claimed defect, and (c) providing proof of purchase. The Dealer/Aquanami will inspect the item and determine whether your claim is covered by this Limited Warranty. You are solely responsible for all costs and expenses associated with the transportation and delivery of items to the Dealer/Aquanami, and any return delivery to you (including, without limitation, delivery of any replacement or repaired Product (or component part)), in connection with any claim for warranty coverage.

Additional Disclaimers and Limitations on Liability

TO THE EXTENT NOT PROHIBITED BY LAW, THIS LIMITED WARRANTY REPRESENTS THE EXCLUSIVE OBLIGATION OF AQUANAMI WITH RESPECT TO THE PRODUCT AND IS IN LIEU OF ALL OTHER REPRESENTATIONS AND WARRANTIES. EXCEPT AS OTHERWISE EXPRESSLY SET FORTH IN THIS LIMITED WARRANTY AND TO THE EXTENT NOT PROHIBITED BY LAW, AQUANAMI DOES NOT MAKE ANY, AND HEREBY EXPRESSLY DISCLAIMS ALL, WARRANTIES, WHETHER EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT AND ITS USE, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ANY WARRANTY OF NON-INFRINGEMENT, AND ANY WARRANTIES THAT MAY ARISE FROM USAGE OF TRADE OR COURSE OF DEALING. SOME STATES DO NOT ALLOW DISCLAIMERS OF IMPLIED WARRANTIES, SO THIS DISCLAIMER MAY NOT APPLY TO YOU. TO THE EXTENT SUCH WARRANTIES CANNOT BE DISCLAIMED UNDER THE LAWS OF YOUR JURISDICTION, WE LIMIT THE DURATION AND REMEDIES OF SUCH WARRANTIES TO THE DURATION OF THE WARRANTY PERIOD STATED ABOVE IN THIS LIMITED WARRANTY.

IN NO EVENT WILL AQUANAMI OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, INCIDENTAL, CONSEQUENTIAL, SPECIAL OR PUNITIVE DAMAGES, OR ANY DAMAGES FOR LOSS OF REVENUE

OR PROFIT, OR LOSS OF TIME OR BUSINESS, ARISING OUT OF OR RELATING TO THE PRODUCT AND/OR ITS USE, WHETHER LIABILITY IS ASSERTED UNDER THEORIES OF TORT, STRICT LIABILITY, CONTRACT, WARRANTY OR OTHERWISE. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

Dispute Resolution, Binding Arbitration and Class Action Waiver

At Aquanami, we are committed to customer satisfaction, so if you have a problem or dispute, we will try to resolve your concerns. But if we are unsuccessful, you may pursue claims as set forth below.

- a. You agree to give us an opportunity to resolve any disputes or claims you may have with Aquanami relating in any way to the Product, its use, or this Limited Warranty (collectively, "Claims") by contacting Aquanami at 10600 West Sam Houston Parkway South, Suite 100, Houston, Taxes 77099, Attn: Customer Service or at service@aquanami.com. If we are not able to resolve your Claims within 60 days, then you may seek relief through arbitration or in small claims court, as set forth below.
- b. YOU AND AQUANAMI AGREE THAT ANY AND ALL CLAIMS WILL BE RESOLVED BY BINDING ARBITRATION, RATHER THAN IN COURT, except that you or Aquanami may assert Claims on an individual basis in small claims court if they qualify. This includes any Claims you assert against us or our affiliates.
- c. THERE IS NO JUDGE OR JURY IN ARBITRATION, AND COURT REVIEW OF AN ARBITRATION AWARD IS LIMITED. HOWEVER, AN ARBITRATOR CAN AWARD ON AN INDIVIDUAL BASIS THE SAME DAMAGES AND RELIEF AS A COURT (INCLUDING STATUTORY DAMAGES, ATTORNEYS' FEES AND COSTS), AND MUST FOLLOW AND ENFORCE THIS LIMITED WARRANTY AS A COURT WOULD.
- d. Arbitrations will be conducted by the American Arbitration Association ("AAA") under its Consumer Arbitration Rules. The AAA's Consumer Arbitration Rules are available at www.adr.org or by calling 1-800-778-7879. The arbitration will be heard and decided by one arbitrator. Payment of all filing, administration and arbitrator fees will be governed by the AAA's Consumer Arbitration Rules, except as otherwise provided in this clause (d). If your total Claims seek less than \$10,000, Aquanami will reimburse you for filing fees you pay to the AAA and will pay arbitrator's fees, unless the arbitrator determines your Claims are frivolous. You may choose to have an arbitration conducted by telephone, based on written submissions, or in person in the state where you live or at another mutually agreed location. Attendance at an in-person hearing may be made by telephone by you and/or Aquanami, unless the arbitrator requires otherwise.
- e. To begin an arbitration proceeding, you must send a letter requesting arbitration and describing your Claims to Aquanami at 10600 West Sam Houston Parkway South, Suite 100, Houston, Taxes 77099, Attn: Legal Department/Arbitration Notice. If we request arbitration against you, we will give you notice at the email address or street address you have provided. A party requesting arbitration must also provide a copy of the request to the AAA, at Case Filing Services, 1101 Laurel Oak Road, Suite 100, Voorhees, NJ 08043 or online at www.adr.org or at any AAA office.

ANY AND ALL PROCEEDINGS (WHETHER IN ARBITRATION OR COURT) TO RESOLVE CLAIMS WILL BE CONDUCTED ONLY ON AN INDIVIDUAL BASIS AND NOT IN A CLASS, CONSOLIDATED OR REPRESENTATIVE ACTION. If for any reason a Claim proceeds in court rather than in arbitration YOU AND AQUANAMI EACH WAIVE ANY RIGHT TO A JURY TRIAL. The Federal Arbitration Act and federal arbitration law apply to this section. An arbitration decision may be confirmed by any court with competent jurisdiction. If any provision set forth in this section entitled "Dispute Resolution, Binding Arbitration and Class Action Waiver" is found unenforceable, the unenforceable provision will be severed from this Limited Warranty and the remaining terms of this Limited Warranty will be enforced.

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS, WHICH VARY FROM STATE TO STATE.

US EPA EMISSION-RELATED WARRANTY

AQUANAMI warrants to the ultimate purchaser and each subsequent purchaser that this new engine, including all parts of its exhaust emission control systems meets two conditions:

- 1. It is designed, built, and equipped so it conforms at the time of sale to the ultimate purchaser with the requirements of 40 CFR 1045 and 40 CFR 1060.
- 2. It is free from defects in materials and workmanship that may keep it from meeting the requirements of 40 CFR 1045 and 40 CFR 1060.

Where a warrantable condition exists, AQUANAMI will repair or replace, as it elects, any part or component with a defect in materials or workmanship that would increase the engine's emissions of any regulated pollutant within the stated warranty period at no cost to the owner, including expenses related to diagnosing and repairing or replacing emission-related parts. All defective parts replaced under this warranty become the property of AQUANAMI.

For all emission-related warranty claims, AQUANAMI is limiting the diagnosis and repair of emission-related parts to the authorized AQUANAMI dealers, unless for emergency repairs as required by item2 of the following list.

As a certifying manufacturer, AQUANAMI will not deny emission-related warranty claims based on any of the following:

- 1. Maintenance or other service AQUANAMI or AQUANAMI 's authorized facilities performed.
- 2. Engine/equipment repair work that an operator performed to correct an unsafe, emergency condition attributable to AQUANAMI as long as the operator tries to restore the engine/equipment to its proper configuration as soon as possible.
- 3. Any action or inaction by the operator unrelated to the warranty claim.
- 4. Maintenance that was performed more frequently than AQUANAMI specifies.
- 5. Anything that is AQUANAMI fault or responsibility.

Emission-Related Warranty Period

The emission-related warranty is valid for the following period whichever comes first:

	HOURS	MONTHS
Exhaust emission-related components	175	30

Components Covered

The emission-related warranty covers all components whose failure would increase an engine's emissions of any regulated pollutant, including the following listed components:

- 1. For exhaust emissions, emission-related components include any engine parts related to the following systems:
 - Air-induction system
 - Fuel system
 - Ignition system
- 2. The following parts are also considered emission-related components for exhaust emissions:
 - Carburetor
 - Fuel pump
 - Spark plug
 - Ignition coil
 - Electric control module
 - Crankcase ventilation valve

Limited Applicability

As a certifying manufacturer, AQUANAMI may deny emission-related warranty claims for failures that have been caused by the owner's or operator's improper maintenance or use, by accidents for which the manufacturer has no

responsibility, or by acts of God. For example, an emission-related warranty claim need not be honored for failures that have been directly caused by the operator's abuse of the engine/equipment or the operator's use of the engine/equipment in a manner for which it was not designed and are not attributable to the manufacturer in anyway.

SECTION 8: CUSTOMER INFORMATION

Watercraft Model Nar	me				
HULL IDENTIFICATION	ON NUMBER (H	I.I.N.)			
ENGINE IDENTIFICA	ATION NUMBER	R (E.I.N.)			
Owner NAME					
STREET					
CITY	STATE /	PROVINCE	ZIP/POS	TAL CODE	
COUNTRY					
Purchase Date	I	I YEAR			
Warranty Expiry Date	el	I YEAR	III MONTH	DAY	
Dealer Name					
Dealer Address					
BY SIGNING BELOW		T I HAVE REA	D AND UNDERSTAN	ND THE FULL A	QUANAMI
Customer Signature X		Date X			